

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
CM	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		A1		REVISED PER ECR-12-007353	18MAY2012	KH	TM
		A2		REVISED PER ECO-20-009442	13JUL2020	WLS	DZ

CIRCUIT 1

CONTACT

HOLDDOWN

HOUSING

(3)

(DIM T)

① MATERIAL: CONTACTS - BRASS
 HOUSING - UL 94V-0 RATED HIGH TEMP NYLON, COLOR BLACK.
 HOLDDOWNS- PHOSPHOR BRONZE.

② PLATING: CONTACTS - 0.76µm MINIMUM GOLD ON MATING END, 2.54µm MINIMUM MATTE TIN ON SOLDER TAILS, BOTH OVER 1.27µm MINIMUM NICKEL.
 HOLDDOWNS- 2.54µm MINIMUM MATTE TIN OVER 1.27µm MINIMUM NICKEL.

③ NO BARE EDGES ALLOWED ON SOLDER TAILS.

④ RECOMMENDED PC BOARD THICKNESS OF 1.57.

PCB LAYOUT COMPONENT SIDE

④

②	27.00	31.43	27.00	34.14	10	1-2029037-0
②	9.00	13.43	9.00	16.14	4	2029037-4
FINISH	DIM Z	DIM V	DIM T	DIM W	NO. OF POSN	PART NUMBER

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN		TE Connectivity	
mm		0 PLC	±	K. WHITAKER	17 JAN 2008		
		1 PLC	±	CHK C. JONES	17 JAN 2008		
		2 PLC	±0.20	APVD C. JONES	17 JAN 2008		
		3 PLC	±	PRODUCT SPEC			
		4 PLC	±	APPLICATION SPEC		NAME	
		ANGLES	±	114-13000		VERT THRU HOLE HEADER ASSY, 0.76 MIC	
		FINISH	±	WEIGHT		GOLD CONTS, W/THRU HOLE HOLDDOWNS,	
MATERIAL	① - SEE TABLE			CUSTOMER DRAWING		SINGLE ROW, MICRO MATE-N-LOK (TM)	
				SCALE 5:1		RESTRICTED TO	
				SHEET 1 OF 1		REV A2	

1471-9 (3/11)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)