



- ① POSITION TOLERANCE APPLIES AT TIP ONLY.
- ② HOUSING: FLAME RETARDENT UL94V-0 RATED, GLASS FILLED NYLON OR POLYESTER, COLOR BLACK. CONTACTS: PHOSPHOR BRONZE. EYELETS: BRASS. SCREWLOCKS: ZINC. BOARDLOCKS: COPPER ALLOY.
- ③ EYELETS: 2.54 μm [.000100] MIN TIN OVER COPPER FLASH. BOARDLOCKS: 3.81 μm [.00015] MIN TIN OVER 1.27 μm [.000050] MIN NICKEL. CONTACTS: 0.76 μm [.000030] MIN GOLD FOR A LENGTH OF 1.52 [.060] MIN FROM MATING END, 2.54 μm [.0001] MIN TIN FOR A LENGTH OF 3.68 [.145] MIN FROM OPPOSITE END, BOTH OVER 1.27 μm [.000050] MIN NICKEL. SCREWLOCKS: CLEAR CHROMATE COATING.

5748989-1
PART NO

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN G. PETERS 22SEP05	Tyco Electronics Corporation Harrisburg, PA 17105-3608
DIMENSIONS: mm [INCHES]		CHK S. BOLASH 22SEP05	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. WALMSLEY 22SEP05	NAME
0 PLC ± -		PRODUCT SPEC	RECEPTACLE ASSEMBLY, SIZE 3, 25 POSN, ALL PLASTIC, RIGHT ANGLE .590 SERIES, AMPLIMITE III
1 PLC ± -		108-1226	
2 PLC ± 0.13 [.005]		APPLICATION SPEC	
3 PLC ± -		114-40027	
4 PLC ± -		WEIGHT	
ANGLES ± z		FINISH	
MATERIAL		FINISH	
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 OF 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)