

4 3 2 1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
D		REVISED PER ECO-17-002903	20MAR2017	AP DG

- 1 RECEPTACLE ACCEPTS SIZE 22 DF SOCKET CONTACTS. CONTACTS MUST BE PURCHASED SEPARATELY.
- 2 ALL PARTS SHIPPED UNASSEMBLED.
- 3 COMPONENTS INDIVIDUALLY BULK PACKAGED.
- 4 ELASTOMER, STYRENE POLYOLEFIN OR PVC, COLOR BLACK.
- 5 FLAME RETARDANT GLASS FILLED, 94V-0 RATED, COLOR BLACK.

- 6 CARBON STEEL PER ASTM A109.
- 7 CARBON STEEL, C1022.
- 8 .000200 MIN TIN PLATE OVER .000100 MIN COPPER UNDERPLATE.
- 9 BLACK ZINC FLAKE COATING.

FERRULE MUST BE PURCHASED SEPARATELY AS REQD BY CABLE DIA

EXPANDING NECK ACCOMMODATES CABLE FROM .338-.562 DIA

#4-40 JACKSCREW QTY:2

SHIELD QTY:2

RECEPTACLE CONN HDP-22

Dimensions: .730 MAX, .125, 2.010 MAX, .600, .812 TYP, 1.467 TYP, 2.865 MAX, 2.500 ±.005

Dimensions: .730 MAX, .125, 2.010 MAX, .600

ENCLOSURE

21, 42, 62, 01, 22, 43

2.500 ±.005

3	W/ LOGOS	5748642-1
PACKAGING	REMARKS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. VARELA - DOCK5 12-21-04	TE TE Connectivity	
DIMENSIONS: INCHES		CHK J. GERACE 12-21-04		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. WALMSLEY 12-21-04	NAME 6	
0 PLC ± -		PRODUCT SPEC 108-40005 & 108-40030	SIZE 4, 62 POSITION, AMPLIMITE, HDP-22	
1 PLC ± -		APPLICATION SPEC 114-40030	SIZE A2	CAGE CODE 00779
2 PLC ± -		WEIGHT 0.000000	DRAWING NO C=5748642	
3 PLC ± .020		CUSTOMER DRAWING	SCALE 2:1	SHEET 1 of 1
4 PLC ± -			REV D	
4 ANGLES ± -				
FINISH				

1471-9 (1/15)

Downloaded From Onevac.com

5748642

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)