



- .035 DIA HOLE IS RECOMMENDED FOR .125 MAX THICK P.C. BOARD
- CONNECTOR MATES WITH ANY AMP 26 POSN PLUG
- POST TIPS WILL FALL WITHIN Ø.020 TRUE POSITION OF EACH OTHER.

- 5 FINISH: CADMIUM PER QQ-P-416
- 6 FINISH: ZINC PLATED PER ASTM-B-633, .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+)

PLATED PER 6	5-211575-1
PLATED PER 5	211575-1
DESCRIPTION	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN 8-11-97		C.C.THOMAS	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		CIRK 11-24-97	
0 PLC ± -		1 PLC ± -		H.WYNKOOP 11-24-97	
1 PLC ± -		2 PLC ± -		NAME	
2 PLC ± -		3 PLC ± .005		H.WYNKOOP	
3 PLC ± -		4 PLC ± -		PRODUCT SPEC	
4 PLC ± -		ANGLES ± -		APPLICATION SPEC	
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS		SIZE CAGE CODE DRAWING NO	
				A1 00779 C=211575	
				RESTRICTED TO	
				CUSTOMER DRAWING	
				SCALE 4:1 SHEET 1 OF 1 REV J	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)