



- 1 EYELETS MUST BE SEATED ON HANDLE AND TIP AS SHOWN. TIP SIDE PLAY NOT PERMISSIBLE.
- 2 SLOTTED SPRING PIN MUST BE SEATED .05 BELOW EACH END OF HANDLE.
- 3 MARKING TO BE CENTERED AND PERMANENTLY MARKED IN AREAS AS SHOWN. (COLOR OPTIONAL).
- 4. TOOL IS SPRING LOADED CLOSED, MUST OPEN AND CLOSE FREELY.
- 5 .010 MAX GAP MEASURED FROM FRONT OF TIP, WITHIN .032 LENGTH.
- 6 MEASURED WITH $\phi .154$ PIN INSERTED INTO .63 TIP LENGTH.

2	A	21920-7	PIN, DOWEL	6
2	A	126217-1	SPRING	5
1	B	445146-1	HANDLE, LEFT SIDE	4
1	B	445145-1	HANDLE, RIGHT SIDE	3
4	B	1-26024-4	EYELET	2
2	B	445144-1	EXTRACTION TIP, HALF	1

-1		DWG SIZE	PART NO	DESCRIPTION	ITEM NO
REVISION OF EACH ASSY NO (WHEN BLANK, USE DWG REVISION)					
PARTS LIST					
QTY REQD PER ASSY		MATERIAL			
		HEAT TREAT		FINISH	
DIMENSIONS IN INCHES. TOLERANCES UNLESS OTHERWISE SPECIFIED:					
2 PLC DEC $\pm .01$					
3 PLC DEC $\pm .005$					
4 PLC DEC \pm					
ANGLES \pm					
SURF TEXTURE: <input checked="" type="checkbox"/>					
REMOVE BURRS, BREAK SHARP EDGES .015R MAX					
DR		12-23-87 APP 1-5-88		AMP INCORPORATED	
M. RITRIVATO		A. J. FLAYNIK		Harrisburg, Pa. 17105	
CHK 1-5-88		REL -			
A. J. FLAYNIK					
NAME: TOOL, EXTRACTION					
SCALE: 2:1		DWG NO: 445147		SHEET 1 of 1 REV C	

P	F	LTR	REVISION RECORD	APP	DATE	P	F	LTR	REVISION RECORD	APP	DATE

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN AMP PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM AMP INCORPORATED, HARRISBURG, PA.

PROD	5069
CODE	DF
LOC	DF
DIST	UO

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)