

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
				変更			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
E4		REVISED ECR-21-107353		14JUL21	T.Q	N.S.	

回路No. 1  
CIRCUIT No. 1

Dimensions: 1.0 (pitch), 6.0 (total height), 3.55 (housing height), 1.55 (contact height), 0.5 (bottom offset).

Dimensions: 0.65 (top width), 0.7 (tip width), 1.5 (total length), 1.0 (bottom width).

キャビティ マーク  
CAVITY MARK

トレード マーク  
TRADE MARK

Dimensions: 1.5 (pitch), 3.6 (total height), 3.0 (housing height), 1.0 (bottom offset), 1.0 (bottom width).

Formulas:  $C = [1.5 \times (\text{Pos}-1) + 1.5 \times 2]$ ,  $A = [1.5 \times (\text{Pos}-1)]$ ,  $B = [1.5 \times (\text{Pos}-1) + 1.0 \times 2]$

2 極  
2 POSITION

注 記

1. 適用電線範囲: AWG #26&#28  
被覆外径:  $\phi 0.8\text{mm} \sim \phi 0.95\text{mm}$
2. 材料: ハウジング-ガラス入りナイロン UL94V-0、色: グレー、青  
コンタクト-錫めっき済み、りん青銅
- ③ ハウジング ロック:  
2極は、1箇所 3~20極は、2箇所
- ④ ゲート口は左付きと右付きが存在する。(2極品を除く)

NOTES:

1. APPLICABLE WIRE SIZE: AWG #26&#28  
INSULATION DIA RANGE:  $\phi 0.8\text{mm} \sim \phi 0.95\text{mm}$
2. MATERIAL:  
HOUSING: NYLON (G.F.) UL94V-0, COLOR: GRAY, BLUE  
CONTACT: PRE-TIN PHOS-BRONZE
- ③ HOUSING LOCK:  
2 POSITION - SINGLE LOCK  
3 TO 20 POSITIONS - DOUBLE LOCK
- ④ CONNECTOR HAVE THE GATE LEFT SIDE AND RIGHT SIDE. (EXCEPT 2Pos.)

DIMENSIONS: 単位: 毫 mm		TOLERANCES UNLESS OTHERWISE SPECIFIED		WIRE RANGE 適合電線断面積 0.08mm <sup>2</sup> - 0.14mm <sup>2</sup>		INSULATION DIA 被覆外径 $\phi 0.8\text{mm} \sim \phi 0.95\text{mm}$	
MATERIAL 材料 SEE NOTE 2 注記2参照		FINISH 仕上 SEE NOTE 2 注記2参照		DWN 12. JUL '96 T. FURUYA		TE Connectivity	
APVD 製品規格 108-5525		APPLICATION SPEC 取付適用規格 114-5223		CHK 12. JUL '96 J. TANIGAWA		NAME 名称 AMP Mini Common Terminated (CT) Connector 1.5mm PITCH MT RECEPTACLE ASSEMBLY	
WEIGHT SEE TABLE 表参照		CUSTOMER DRAWING		SIZE A3		DRAWING NO 番号 C=353293	
SCALE 尺度 NON		SHEET 1 OF 2		REV E4			

Downloaded From Oneyac.com

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1			


0.97	31.5	30.5	28.5	20	7-353293-0	4-353293-0	2-353293-0
0.92	30.0	29.0	27.0	19	6-353293-9	3-353293-9	1-353293-9
0.87	28.5	27.5	25.5	18	6-353293-8	3-353293-8	1-353293-8
0.83	27.0	26.0	24.0	17	6-353293-7	3-353293-7	1-353293-7
0.78	25.5	24.5	22.5	16	6-353293-6	3-353293-6	1-353293-6
0.73	24.0	23.0	21.0	15	6-353293-5	3-353293-5	1-353293-5
0.68	22.5	21.5	19.5	14	6-353293-4	3-353293-4	1-353293-4
0.64	21.0	20.0	18.0	13	6-353293-3	3-353293-3	1-353293-3
0.59	19.5	18.5	16.5	12	6-353293-2	3-353293-2	1-353293-2
0.54	18.0	17.0	15.0	11	6-353293-1	3-353293-1	1-353293-1
0.49	16.5	15.5	13.5	10	6-353293-0	3-353293-0	1-353293-0
0.45	15.0	14.0	12.0	9	5-353293-9	2-353293-9	353293-9
0.40	13.5	12.5	10.5	8	5-353293-8	2-353293-8	353293-8
0.35	12.0	11.0	9.0	7	5-353293-7	2-353293-7	353293-7
0.30	10.5	9.5	7.5	6	5-353293-6	2-353293-6	353293-6
0.26	9.0	8.0	6.0	5	5-353293-5	2-353293-5	353293-5
0.21	7.5	6.5	4.5	4	5-353293-4	2-353293-4	353293-4
0.16	6.0	5.0	3.0	3	5-353293-3	2-353293-3	353293-3
0.11	4.5	3.5	1.5	2	5-353293-2	2-353293-2	353293-2
WEIGHT (g)	C	B	A	Pos.	BLUE	BLACK	GRAY
	寸法 DIMENSIONS				製品型番 P/N		

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

THIS DRAWING IS UNPUBLISHED.

COPYRIGHT

DIMENSIONS: 単位: ㎜ mm		WIRE RANGE 絶縁電線断面積 0.08mm <sup>2</sup> -0.14mm <sup>2</sup>		INSULATION DIA 被覆外径 Ø0.8mm-Ø0.95mm	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差 10 > : ±0.2 30 > : ±0.25 100 > : ±0.3 ANGLE : ±3°		MATERIAL SEE SHEET 1 OF 2 材料   枚目参照		FINISH SEE SHEET 1 OF 2 仕上   枚目参照	
DWN T. FURUYA 12. JUL '96 CHK J. TANIGAWA 12. JUL '96 APVD		 TE Connectivity			
PRODUCT SPEC 製品規格 108-5525		NAME 名称 AMP Mini Common Terminated (CT) Connector 1.5mm PITCH MT RECEPTACLE ASSEMBLY			
APPLICATION SPEC 取付適用規格 114-5223		SIZE	CAGE CODE	DRAWING NO	
WEIGHT SEE TABLE 表参照		A4	00779	C=353293	
CUSTOMER DRAWING				SCALE 尺度	NON
				SHEET	2 OF 2
				REV	E4

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)