

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
	G	REV PER ECO 14-017026		11-11-14	CT	DE	

Top view showing concentric circles. Outer diameter is $\phi 1.12$ REF. Inner diameter is $\phi 0.062$ PIN.

Side view showing dimensions: total length 1.95, length to start of thread 1.812, thread length .38 MIN FULL THD, diameter $\phi 0.312$, distance from end to start of thread .030, distance from end to center of hole 1.20, and hole diameter $\phi 0.070$ REF. Thread specification: 3/4-16 UNF-2A THD.

⚠ SCREW THREAD MEASUREMENT IN ACCORDANCE WITH H28 HANDBOOK (3 WIRE METHOD) USING WIRE .03608 DIA MEASUREMENT OVER WIRE SHALL BE .7654/.7474

- THIS RECEPTACLE IS HERMETICALLY SEALED.
- MARKED PER MIL-STD-130.

TIN PLATED	5-861257-1
TIN-LEAD PLATED	861257-1
PIN & FLANGE FINISH	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	7-14-06	C.C.THOMAS	
DIMENSIONS: INCHES		CHK	7-14-06	D.EABY	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	7-14-06	D.EABY	
0 PLC ± -		PRODUCT SPEC			
1 PLC ± -		APPLICATION SPEC			
2 PLC ± .01		-			
3 PLC ± .005		-			
4 PLC ± -		-			
ANGLES ± 1°		-			
MATERIAL: MOLDED GLASS EPOXY		FINISH	SEE TABLE		
WEIGHT		-		SIZE	A2
CUSTOMER DRAWING		CAGE CODE	00779	DRAWING NO	861257
SCALE		3:1		SHEET	1 of 1
REV		G			

1471-9 (3/11)

Downloaded From Onevac.com

861257

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)