



USED ON

ELECTRICAL

1. MILLIVOLT-TEMPERATURE CHARACTERISTIC: SEE THERMOCOUPLE OUTPUT TABLE
2. LIMITS OF ERROR: STANDARD.
3. INSULATION RESISTANCE: 1.000 MEGOHMS MINIMUM AT 500 VOLTS D.C., LEADS TO CASE.

MECHANICAL

1. JUNCTION: SEE TABLE.
2. LEADWIRE: AWG #24, SOLID, TEFLON INSULATED, WITH TEFLON JACKET OVERALL.
3. LEAD TERMINATION: MINI FLAT PIN, THERMOCOUPLE PLUG, SUPPLIED WITH MATING JACK.
4. CASE: STAINLESS STEEL.
5. TEMPERATURE RANGE: -50°C TO 250°C (EXCLUDING PLUG/JACK).

Part Number	Thermocouple Type	Y' Cable Length
200092-10-00	Type J (Iron - Constantan)	36.0"
200092-10-01	Type K (Chromel - Alumel)	36.0"
200092-10-02	Type T (Copper - Constantan)	36.0"

EAR CONTROLLED

Technical information subject to the U.S. Export Administration Regulations (EAR). This technical information is prohibited from transfer or disclosure in any manner to non-U.S. persons in the United States or abroad without prior approval by the U.S. Commerce Department or EAR exemption.

This drawing and the information thereon are the property of Measurement Specialties Inc. a TE Connectivity CO. all unauthorized use and reproduction is prohibited.

NO CHANGES TO BE MADE TO THIS DRAWING WITHOUT APPROVAL OF MEAS TPG ANDOVER

REVISION RECORD	P	LTR	DATE	DMN	APVD

DIMENSIONS:	INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC	± .020	
1 PLC	± .010	
3 PLC	± .005	
4 PLC	± .005	

DMN	CHK	APVD	NAME	MATERIAL	HEAT TREAT
04.24.19			TC, Capsule, Cable, Mini Connector		



3508-7 (1/15)

SCALE	SIZE	DRAWING NO	SHEET	OF	REV
NTS	A3	20009210	1	1	A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)