



- △ ZINC.
- △ STAINLESS STEEL.
- 3. TO ASSEMBLE JACKSCREW REFER TO INSTRUCTION SHEET #1189.
- △ HOLE CENTRALLY LOCATED WITHIN ±0.07 [.003] OF THE 5.54 [.218] DIA AND THE 2.77/2.84 [.109/.112] DIA CENTER LINES.
- △ CHROMATE CONVERSION, CLEAR WITH HEXAVALENT CHROMATE.
- △ CHROMATE CONVERSION, CLEAR W/O HEXAVALENT CHROMATE.

| | | | |
|----------|---|-------------|-------------|
| OBSELETE | △ | 2.87 [.113] | 201910-5 |
| | - | 2.11 [.083] | 201910-3 |
| | △ | 2.87 [.113] | 201910-1 |
| NOTES | A | | PART NUMBER |

| | | | | |
|---|--|---|---|-------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN K. FOLTZ 05/26/94 | Tyco Electronics Corporation Harrisburg, PA 17105-3608 | |
| DIMENSIONS: mm [INCHES] | | CHK R. STONE 06/16/94 | APVD | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | NAME JACKSCREW KIT, UNASSEMBLED, FEMALE, M SERIES | | |
| 0 PLC ± - | | PRODUCT SPEC | | |
| 1 PLC ± - | | APPLICATION SPEC | | |
| 2 PLC ± 0.13 [.005] | | SIZE A1 | | |
| 3 PLC ± - | | CAGE CODE 00779 | | |
| 4 PLC ± - | | DRAWING NO 201910 | | |
| ANGLES ± - | | RESTRICTED TO | | |
| MATERIAL JACKSCREW BODY: △ JACKSCREW TIP: △ JACKSCREW PIN: △ | | FINISH JACKSCREW BODY: SEE NOTES JACKSCREW PIN: PASSIVATE | | WEIGHT - |
| CUSTOMER DRAWING | | SCALE 4:1 SHEET 1 OF 1 REV L1 | | |

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)