



PCB Layout

REVISIONS				
NO.	DESCRIPTION	DATE	BY	APP'D
1	UPDATE DESCRIPTION	2002/09/25	GF	SM
2	UPDATE DESCRIPTION			
3	UPDATE DESCRIPTION			

NO.	DESCRIPTION	DATE	BY	APP'D
1	HOUSING			
2	CONTACT			
3	LEVER			
4	COVER			
5	SPRING			

NO. OF POSITIONS	PART NO
2 POSN	2834080-1
3 POSN	2834080-2
4 POSN	2834080-3
5 POSN	2834080-4
6 POSN	2834080-5
7 POSN	2834080-6
8 POSN	2834080-7

NOTES :

△ MATERIALS AND FINISH:
 - HOUSING: PA66
 - CONTACTS: BRASS, FINISH: TIN OVER NICKEL UNDERPLATE

- MUST COMPLY WITH DIRECTIVE 2002/95/EC (RoHS)
- WIRE TYPES AND SIZES ACCEPTED
 WIRE RANGE: 12AWG~28AWG.
 STRIP LENGTH: 5~6mm
- PACKAGED IN TRAY.
- CURRENT RATING: 20Amp AC300V.
- OPERATION TEMPERATURE: -40°C TO +105°C
- THIS PART NO. IS THE SAME STRUCTURE AS THE SERIES: 2834080
- THE DATASHEET AND MORE DETAILS PLEASE FOLLOW THE SERIES: 2834080

THIS DRAWING IS A CONTROLLED DOCUMENT

IMPROVE FU 200202015
 SHI LANG 200202015

DATE: 10/20/2015
 PRODUCT CODE: 109-137148
 PART NUMBER: 114-137148
 VERSION: -

CUSTOMER DRAWING

5.00mm Horizontal Entry Screwless Connector

SCALE: 1:1

REV: 3

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)