



- 1 POLYESTER,PBT,BLACK,PER MIL-M-24519
- 2 POLYESTER,PBT,NATURAL,PER MIL-M-24519
- 3 ZINC PER QQ-Z-363
- 4 PHOSPHOR BRONZE PER QQ-B-750
- 5 TIN PLATE PER ASTM-B-545
- 6 GOLD PL PER MIL-G-45204
- 7 RESISTOR CHARACTERISTICS:  
A. OHMS (SEE TABLE)  
B. 5% TOLERANCE  
C. 400mW POWER RATING
- 8 SELECTIVELY GOLD PLATED ON INTERFACE AREA PER: MIL-G-45204, .000030 THK,TIN PLATE ON SOLDER TAIL PER: ASTM-B-545, ALL OVER NICKEL PL PER: QQ-N-290
- 9. BOARD THICKNESS: .062 MAX

P.C.B. CONFIGURATION  
SCALE= 10:1

RECOMMENDED  
PANEL CUTOUT

2.67±0.38 [.105±.015]	2.79 [.110]	75 OHMS	5414367-2
C	B	RESISTOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN G. ATTADIA - 01FEB2005	 Tyco Electronics Corporation Harrisburg, Pa 17105-3608
DIMENSIONS: mm [INCHES]		CHK J. HAVENER - 01FEB2005	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. LIPPERT - 01FEB2005	NAME JACK,PCB,RIGHT ANGLE, SELF-TERMINATING BNC
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± 0.20 [.008]
4 PLC ± -	ANGLES ± -	APPLICATION SPEC	
MATERIAL		FINISH	
WEIGHT		SIZE	
CUSTOMER DRAWING		SCALE 5:1 SHEET 1 OF 1 REV 0	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)