
Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number : 234A011 thru 052-XXS

Boot, Rectangular, D-Subminiature, 90°, Side Entry, with Heat Recoverable Screen Description :

1. All dimensions are in $\frac{\text{III.III.o.}}{[\text{millimeters}]}$

- 2. Dimensions appearing in table are as follows:
 - a As Supplied
 - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added entry diameters will be reduced by .06 max.
 - a- Conductive thermoplastic adhesive
 - b- Structural thermoplastic adhesive






TABLE OF DI	MENSIC	NS											
PART	Н		J		к		Р	R	s		U	w	×
NUMBER	Min	Max	Min	Max	Min	Max	Ref	Ref	Ref	Min	±20%	±20%	±20%
	a	b	a	ь	a	b	b	b	ь	a	b	b	ь
234A011-XXS	.82	.80	.62	. <u>42</u>	.35	<u>16</u>	1.02	. <u>87</u>	<u>.59</u>	.12	. <u>18</u>	.04	.12
	[20,8]	[20,3]	[15,7]	[10,7]	[9,0]	[4,1]	[26,0]	[22,0]	[15,0]	[3,0]	[4,6]	[1,0]	[3,0]
234A021-XXS	1.14	1.11	.62	. <u>42</u>	.43	.21	1.22	. <u>98</u>	<u>.75</u>	.15	.26	.04	.12
	[29,0]	[28,2]	[15,7]	[10,7]	[11,0]	[5,3]	[31,0]	[25,0]	[19,0]	[3,8]	[6,5]	[1,0]	[3,0]
234A032-XXS	1.69	1.66	.62	.42	.59	.32	1.69	1 <u>.10</u>	. <u>87</u>	.20	.30	.04	.12
	[42,8]	[42,2]	[15,7]	[10,7]	[15,0]	[8,1]	[43,0]	[28,0]	[22,0]	[5,0]	[7,5]	[1,0]	[3,0]
234A036-XXS	2.40	<u>2.17</u>	.55	. <u>42</u>	.78	. <u>41</u>	2.08	1 <u>.53</u>	1 <u>.30</u>	.20	. <u>39</u>	.04	.12
	[61.0]	[55,1]	[14,0]	[10,7]	[20,0]	[10,6]	[53,0]	[39,0]	[33,0]	[5,0]	[10,0]	[1,0]	[3,0]
234A042-XXS	2.34	2.31	.59	<u>.42</u>	.75	.34	2.09	1 <u>.18</u>	<u>.98</u>	.24	<u>.39</u>	.04	.12
	[59,5]	[58,7]	[15,0]	[10,7]	[19,0]	[8,6]	[53,0]	[30,0]	[25,0]	[6,0]	[10,0]	[1,0]	[3,0]
234A052-XXS	2.26	2.28	.65	<u>.54</u>	.75	<u>.42</u>	2.20	1 <u>.26</u>	<u>.98</u>	.24	. <u>39</u>	.04	.12
	[57,5]	[57,9]	[16,5]	[13,7]	[19,0]	[10,7]	[56,0]	[32,0]	[25,0]	[6,0]	[10,0]	[1,0]	[3,0]

AYCHEM CORPORATION DO CONSTITUTION DRIVE ENLO PARK, CALIFORNIA 94025

Revision: E Date: 5/5/99 Part Number :

234A011 thru 052-XXS

Description:

Boot, Rectangular, D-Subminiature, 90°, Side Entry, with Heat Recoverable Screen


Thermofit Molded Parts Specification Control Drawing Limited Distribution

234A011 THRU 052-XXS Part Number :

Description:

Boot, Rectangular, D-Subminiature, 90°, Side Entry, with Heat Recoverable Screen

ATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION	
olyolefin/Copper Composite	RT-1370	/200	N/A	Adhesives	
astomer/Copper Composite	RT-1371	/200	N/A	Adhesives	
ol	yolefin/Copper Composite	yolefin/Copper Composite RT-1370	yolefin/Copper Composite RT-1370 /200	yolefin/Copper Composite RT-1370 /200 N/A	



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

If this document is printed it becomes uncontrolled Check for the latest revision.

234A011 thru 052-XXS Part Number: Description:

Boot, Rectangular, D-Subminiature, 90°, Side Entry, with Heat Recoverable Screen

Downloaded From Oneyac.com

Revision : E

Date: 5/5/99

CAD FILE MP99092

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)