

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
G	86	D	REV PER ECO-11-017213	12DEC11	PY BW

1.84 MAX

ASTERISK NEAR SIDE

ASTERISK FAR SIDE

SEE TABLE FOR PART NUMBER $\triangle 2$

ASTERISK REF

.372 REF

.072 REF

.41 MAX DIA

NOTCH ORIENTED OPPOSITE ASTERISK

ASTERISK REF

1 WIRE INSULATION: .260-.298 DIA

$\triangle 2$ STAMP " 696847-x AMP 6AL-8CU 13-78"
 SIZE AND LOCATION APPROX AS SHOWN

.79 MIN TYP CONDUCTOR DEPTH

.32-.37 TYP INSULATION DEPTH

INSERT SCREEN TYP

FUNNEL TYP

ϕ .31 MIN TYP

ϕ .23 MIN TYP

SECTION A-A

BODY: COPPER ASTM-B187 ANNEALED TIN PL PER ASTM B-545 .000150 MIN THK INSERT & FUNNEL: BRASS ASTM B36 NICKEL PL SAE AMS QQ-N-290A, DATED JULY 2000, 0.00254 [.000100] MIN THK	696847-1
MATERIAL & FINISH	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	JR RUTH	08NOV06	 TE Connectivity
DIMENSIONS: INCHES		CHK	MS FEHER	08NOV06	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	MJ SPICER	08NOV06	
0 PLC ± - 1 PLC ± - 2 PLC ± .008 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC	NAME		
MATERIAL SEE TABLE		FINISH	SEE TABLE		WIRE SPLICE, BUTT, SEALED COPALUM 6 AL - 8CU
WEIGHT - GRAMS		A2 00779		C=696847	RESTRICTED TO
CUSTOMER DRAWING		SCALE	3:1	SHEET	1 of 1

1471-9 (3/11) Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)