



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 <sub>1</sub>	SEE ECN 80-0084	GB 1/22/80	TS 1/23/80
03 <sub>0</sub>	CHANGED REV PER ECN 88-0651	GS 3/24/88	
03 <sub>1</sub>	REDRAWN IN CAD, ECN 88-0678	<i>OGM</i> 10/7/91	<i>BB</i> 10/9/91

HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
COMPONENT	MATERIAL	FINISH

CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.089
CONTACT	.023

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCE ON  
FRAC. DEC. ANGLES  
± 1/64 ± .005 ± °

These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

DRAWN BY ES DATE 3/14/68  
CHECKED BY PRB 3/14/68  
APPRD BY D.NANIA 3/14/68

USE ASS'Y PROCEDURE

NO. AP. 10-002  
408-04795

**AMP** *AMP Incorporated*  
140 Fourth Avenue  
Waltham, MA 02451-7599

TITLE OSSM STRAIGHT  
CABLE PLUG  
DIRECT SOLDER ATTACHMENT

SIZE B	CODE IDENT NO. 26805	1001-5004-00	REV 03 <sub>1</sub>
SCALE 8:1		SHEET 1 OF 1	

NOTES:  
1. DESIGNED FOR USE WITH .085 DIA  
SEMI-RIGID CABLE

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)