



RECOMMEND PCB Layout

NOTES :

REV	DATE	BY	APP'D
1			

- △ MATERIALS AND FINISH:
- HOUSING: PA66
 - CONTACTS: COPPER ALLOY, FINISH: TIN OVER NICKEL UNDERPLATE
 - SPRING: STAINLESS STRIP STEEL

- MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
- WIRE TYPES AND SIZES ACCEPTED
 WIRE RANGE: 14AWG~20AWG.
 STRIP LENGTH: 9.0mm~10mm
- PACKAGED IN TRAY.
- CURRENT RATING: 10Amp AC300V.
- OPERATION TEMPERATURE: -40°C TO +105°C

P/N: *-2834018-*

COLOR CODE: _____ PIN No: _____

SERIES CODE	POSN
1=GREEN	2=2 POSN
2=BLUE	3=3 POSN
3=BROWN	4=4 POSN
4=ORANGE	5=5 POSN
5=GREY	6=6 POSN
6=RED	7=7 POSN
7=YELLOW	8=8 POSN
8=PURPLE	
9=WHITE	
0=BLACK	

REMARK: THE DIFFERENT COLORS COULD BE COMBINED TO THE NEW CONNECTOR P/Ns FOR CUSTOMER REQUEST.

REV	DESCRIPTION	DATE	BY	APP'D
1	FIRST VERSION			

40.9	8 POSN
35.9	7 POSN
30.9	6 POSN
25.9	5 POSN
20.9	4 POSN
15.9	3 POSN
10.9	2 POSN
A	NO. OF POSITIONS

THIS DRAWING IS A CONTROLLED DOCUMENT.

DESIGNER	CHK'D	DATE	REV
SHI MING	15JAN2015		
108-137082	114-137082		
108-137082	114-137082		

5.0mm Pitch Modular Screwless Conn

STC TE Connectivity

SIZE 1 CODE 00779

SCALE 1:1

REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)