

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - N/A .

© COPYRIGHT N/A BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

PART NO.	A	FINISH	
836917-1	25.75 [654.0]	∇	OBSOLETE
836917-2	23.00 [584.2]	∇	OBSOLETE
836917-3	28.00 [711.2]	∇	OBSOLETE
836917-4	12.75 [323.8]	∇	
836917-5	6.00 [152.4]	∇	OBSOLETE
836917-6	66.00 [1676.4]	∇	
836917-7	20.00 [508.0]	∇	
836917-8	16.00 [406.4]	∇	
836917-9	12.00 [304.8]	∇	OBSOLETE
1-836917-0	36.00 [914.4]	∇	OBSOLETE
1-836917-1	54.00 [1371.6]	∇	OBSOLETE
1-836917-2	22.00 [558.8]	∇	OBSOLETE
1-836917-3	72.00 [1828.8]	∇	OBSOLETE
1-836917-4	18.00 [457.2]	∇	
1-836917-5	48.00 [1219.2]	∇	OBSOLETE
1-836917-6	15.00 [381.0]	∇	
1-836917-7	10.00 [254.0]	∇	OBSOLETE
1-836917-8	30.00 [762.0]	∇	
1-836917-9	4.00 [101.6]	∇	OBSOLETE
2-836917-0	8.00 [203.2]	∇	OBSOLETE
2-836917-1	97.00 [2463.8]	∇	OBSOLETE
2-836917-2	9.00 [228.6]	∇	OBSOLETE
2-836917-3	23.62 [599.9]	∇	OBSOLETE
2-836917-4	39.36 [999.7]	∇	OBSOLETE
2-836917-5	24.00 [609.6]	∇	OBSOLETE
2-836917-6	17.00 [431.8]	∇	
2-836917-7	14.00 [355.6]	∇	OBSOLETE
2-836917-8	16.50 [419.1]	∇	
2-836917-9	27.00 [685.8]	∇	OBSOLETE
3-836917-0	60.00 [1524.0]	∇	OBSOLETE
3-836917-1	13.00 [330.2]	∇	OBSOLETE
3-836917-2	21.50 [546.1]	∇	OBSOLETE
5-836917-6	66.00 [1676.4]	∇	

LOC	DIST	REVISIONS					
DF	S0	P	LTR	DESCRIPTION	DATE	DWN	APVD
		S		REV PER 0H14-0191-05	05-05	AA	DE

- ∇ .300 MAX DIMENSION HELD OVER THE .910 MAX AREA ONLY.
- MARKED PER MIL-STD-130.
- LEADS WILL MATE WITH AMP LGH-1 & 1L RECEPTACLES.
- ∇ TOLERANCE OF LEAD LENGTH:
UP TO 24 INCHES [609.6] = \pm .12 [\pm 3.0]
24 INCHES [609.6] & UP = \pm 1%
- OPERATING VOLTAGE: 25 KVDC AT 0 TO 70,000 FEET, -55°C TO 125°C.
- ∇ CONNECTOR TO MATE WITH J1-21 TERMINAL.
- ∇ PLATED 93/7 TIN-LEAD OR TIN PER ASTM-B-545 OVER NICKEL PER AMS-QQ-N-290.
- ∇ PLATED TIN PER ASTM-B-545 OVER NICKEL PER AMS-QQ-N-290.

Technical drawing of a lead assembly. Dimensions include: A (total length), .910 MAX [23.11], ∇ .300 MAX [7.62], .53 MAX [13.46], ϕ .84 MAX [21.33], ϕ .280 [7.11], ϕ .265 [6.73], 1.74 MAX [44.19], .12 MAX [3.0], ϕ 1.58 MAX [40.13]. Callouts include: SOCKET; SIZE #16, MAT'L: COPPER ALLOY PER QQ-B-626, FINISH: GOLD PER ASTM-B-488 OVER NICKEL PER QQ-N-290; "O" RING, SILICONE RUBBER; WASHER, TEFLON QTY = 2; CAP MAT'L: POLYCARBONATE MLDG. CMPD. COLOR: RED; #16 AWG SILICONE LEAD WIRE COLOR: WHITE; MOLDDED END SILICONE RUBBER; J1-21 CONTACT MAT'L: CARBON STEEL PER ASTM-A-109 FINISH: ∇ ∇ ; "O"-RING SILICONE RUBBER.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	21-FEB-90	 Tyco Electronics Corporation Harrisburg, Pa 17105-3608			
DIMENSIONS:		CHK	28-FEB-90				
INCHES		APVD	28-FEB-90				
		NAME	S.GLATFELTER				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		LEAD ASSEMBLY LGH-1, LGH-1L WITH J1-21 CRT END			
0 PLC \pm -		APPLICATION SPEC		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
1 PLC \pm -				A2	00779	C=836917	-
2 PLC \pm -		WEIGHT	-	SCALE	1:1	SHEET	1 OF 1
3 PLC \pm -		CUSTOMER DRAWING		REV	S		
4 PLC \pm -							
ANGLES \pm -							
FINISH							
SEE CALLOUTS							

AMP 1471-9 REV 31MAR2000

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)