



- ① HOUSING FULLY LOADED WITH CONTACTS.
- ② NUMBER ON CONTACT INDICATES WIRE RANGE.
- ③ CONTACT INSULATION RANGE: .060 MAXIMUM O.D.
- ④ CONTACTS PLATED .000030 GOLD ON MATING END FOR .100 MIN LENGTH. .000100-.000200 THICK BRIGHT TIN OR BRIGHT TIN-LEAD IN AREA SHOWN. .000050 THICK NICKEL UNDERPLATE ON ENTIRE CONTACT.
- ⑤ CONTACTS PLATED WITH GOLD FLASH ON MATING END FOR .100 MIN LENGTH. .000100-.000200 THICK BRIGHT TIN OR BRIGHT TIN-LEAD IN AREA SHOWN. .000030 THICK NICKEL UNDERPLATE ON ENTIRE CONTACT.
- ⑥ CONTACTS PLATED .000030 GOLD ON MATING END FOR .100 MIN LENGTH. .000100-.000200 THICK MATTE TIN IN AREA SHOWN. .000050 THICK NICKEL UNDERPLATE ON ENTIRE CONTACT.
- ⑦ CONTACTS PLATED WITH GOLD FLASH ON MATING END FOR .100 MIN LENGTH. .000100-.000200 THICK MATTE TIN IN AREA SHOWN. .000030 MIN THICK NICKEL UNDERPLATE ON ENTIRE CONTACT.
- ⑧ HOUSING: BLACK THERMOPLASTIC 94V-0 RATED. CONTACTS: PHOSPHOR BRONZE.

	②	2	#22-26	745201-9
OBSOLETE	③	3	#20-22	745201-8
	④	2	#22-26	745201-7
SUPD BY 745201-3	⑤	3	#20-22	745201-6
OBSOLETE	⑥	2	#22-26	745201-5
OBSOLETE	⑦	1	#26-30	745201-4
OBSOLETE	⑧	3	#20-22	745201-3
OBSOLETE	⑨	2	#22-26	745201-2
OBSOLETE	⑩	1	#26-30	745201-1
	FINISH	②	AWG WIRE RANGE	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN	11-15-04
0. PLC ± -	1. PLC ± -	L. VARELA - DOCKS	11-15-04
2. PLC ± -	3. PLC ± .005	J. GERACE	11-15-04
4. PLC ± -	ANGLES ± °	M. WALMSLEY	11-15-04
MATERIAL	FINISH SEE TABLE	APVD	NAME
⑧			

STE TE Connectivity

ASSEMBLY RECEPTACLE, SIZE 1, 9 POSITION, AMPLIMITE

108-40011

114-40002

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 745201

WEIGHT: -

CUSTOMER DRAWING SCALE: 4:1 SHEET: 1 OF 1 REV: M2

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)

[>>点击查看相关商品](#)