



RECOMMENDED HOLE LAYOUT

- 1 TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
- 2 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- 3 POINT OF MEASUREMENT FOR PLATING THICKNESS.
- 4 OBSOLETE PART NUMBER.
- 5 RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
- 6 FOR 2 POSITION PART ONLY, THE NOTED DIMENSION IS .184
- 7 M FOR KINKED TAILS
- 8 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

8	3.284	3.200	32	66	2-104433-4
OBSOLETE	1.784	1.700	17	36	2-104433-3
	3.484	3.400	34	70	2-104433-2
	2.184	2.100	21	44	2-104433-1
	3.984	3.900	39	80	2-104433-0
8 OBSOLETE	2.984	2.900	29	60	1-104433-9
	2.484	2.400	24	50	1-104433-8
	1.984	1.900	19	40	1-104433-7
8 OBSOLETE	1.684	1.600	16	34	1-104433-6
	1.484	1.400	14	30	1-104433-5
	1.384	1.300	13	28	1-104433-4
	1.284	1.200	12	26	1-104433-3
8 OBSOLETE	1.184	1.100	11	24	1-104433-2
	1.084	1.000	10	22	1-104433-1
	.984	.900	9	20	1-104433-0
8 OBSOLETE	.884	.800	8	18	1-104433-9
	.784	.700	7	16	1-104433-8
8 OBSOLETE	.684	.600	6	14	1-104433-7
	.584	.500	5	12	1-104433-6
	.484	.400	4	10	1-104433-5
	.384	.300	3	8	1-104433-4
	.284	.200	2	6	1-104433-3
	.184	.100	1	4	1-104433-2
	.084	—	—	2	1-104433-1
	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN H MOLL 23JUN88	CHK R FEJDT 23JUN88	APVD R FEJDT 23JUN88	NAME
0. PLC ± -	1. PLC ± -	TE Connectivity HEADER ASSY, MOD II, BREAKAWAY, DBL ROW, 100X.100 C VERT, .025 SQ POSTS, WITH RETENTION FEATURE			PRODUCT SPEC
2. PLC ± -	3. PLC ± .005				APPLICATION SPEC
4. PLC ± -	ANGLES ± -				SIZE CAGE CODE DRAWING NO
					WEIGHT
MATERIAL: HOUSING: FLAME RETARDANT THERMOPLASTIC COLOR: BLACK	FINISH: POSTS: .00015 GOLD IN CONTACT AREA .00010-.00020 WHITE TIN LEAD ON SOLDER TAIL, ALL OVER .00050 NICKEL	CUSTOMER DRAWING		SCALE 4:1	SHEET 1 of 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)