

- MATERIAL:
HOUSING - THERMOPLASTIC POLYESTER, GLASS FILLED, UL94-0.
POST - COPPER ALLOY
- FINISH:
HOUSING - BLACK
POST - SEE NOTES 12, 13 AND 14 FOR PLATING.
- POST TO WITHSTAND 3LBS (16N) MIN AXIAL FORCE IN THIS DIRECTION WITHOUT DISLODGING.
- APPLIES AT -A-.
- APPLIES WHEN HEADER IS STRAIGHT.
- PLASTIC PROJECTIONS PERMITTED IN THIS ZONE.
- COORDINATE DIMENSIONS APPLIES FROM CENTER OF ACTUAL FEATURE.
- SOLDER SIDE OF BOARD IS SHOWN.
- POST SOLDERTAIL MUST COMPLY WITH AMP SOLDERABILITY SPEC 109-11-2.
- LATCH DETENT FEATURE APPEARS 1 PLACE ON EACH END OF PART (MAX OF 2 PER PART) ON ALL POSITIONS 4 THRU 12. THE LATCH APPEARS ONLY ONE PLACE ON 2 & 3 POSITION PARTS.
- DIMENSIONS IN BRACKETS ARE IN INCHES.
- PLATING: GOLD PLATE AREA, 0.00038 [.000015] GOLD OR 0.00008 [.000003] MIN GOLD FLASH OVER 0.00030 [.000012] PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, ALL SIDES, OVER NICKEL UNDERPLATE, 0.00127 [.000050] MIN, ALL SIDES AND ENTIRE LENGTH OF POST.
- BRIGHT TIN LEAD (93/7) PLATE AREA 0.00381 - 0.0089 [.000150 - .000350] ALL FOUR SIDES, 3.18 [.125] MIN..
- MATTE TIN PLATE AREA 0.00381 - 0.0089 [.000150 - .000350] ALL FOUR SIDES, 3.18 [.125] MIN..
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI


PLATING	MM	IN	NO. OF POSN	PART NUMBER
	49.94	1.966	12	3-647141-2
	45.97	1.810	11	3-647141-1
	42.01	1.654	10	3-647141-0
	38.05	1.498	9	2-647141-9
	34.09	1.342	8	2-647141-8
	30.12	1.186	7	2-647141-7
	26.16	1.030	6	2-647141-6
	22.20	.874	5	2-647141-5
	18.24	.718	4	2-647141-4
	14.27	.562	3	2-647141-3
	10.31	.406	2	2-647141-2
	49.94	1.966	12	1-647141-2
	45.97	1.810	11	1-647141-1
	42.01	1.654	10	1-647141-0
	38.05	1.498	9	-647141-9
	34.09	1.342	8	-647141-8
	30.12	1.186	7	-647141-7
	26.16	1.030	6	-647141-6
	22.20	.874	5	-647141-5
	18.24	.718	4	-647141-4
	14.27	.562	3	-647141-3
	10.31	.406	2	647141-2

- 647141-6 SHOWN
- 12 SUPERSEDED BY 3-647141-2
 - 11 SUPERSEDED BY 3-647141-1
 - 10 SUPERSEDED BY 3-647141-0
 - 9 SUPERSEDED BY 2-647141-9
 - 8 SUPERSEDED BY 2-647141-8
 - 7 SUPERSEDED BY 2-647141-7
 - 6 SUPERSEDED BY 2-647141-6
 - 5 SUPERSEDED BY 2-647141-5
 - 4 SUPERSEDED BY 2-647141-4
 - 3 SUPERSEDED BY 2-647141-3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN B LEWIS 16JUN98	APVD R SWING 16JUN98	NAME
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± .005	4 PLC ± -
ANGLES ± -				
MATERIAL	FINISH	WEIGHT	SIZE CAGE CODE DRAWING NO	RESTRICTED TO
			A1 00779 C=647141	
CUSTOMER DRAWING		SCALE 5:1	SHEET 1 OF 1	REV E

STE TE Connectivity
 MTA-156 SHROUDED HEADER ASSEMBLY, RIGHT ANGLE FRONT BEND .045 SQUARE POST, .000015 GOLD, W/O RETENTION PEG



单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)