


CUSTOMER DRAWING




MATERIALS

1. INSULATION SLEEVE: Heat shrinkable, transparent blue, radiation cross-linked polyvinylidene fluoride.
2. SOLDER PREFORM WITH FLUX:
 - SOLDER: TYPE Sn63 per ANSI J-STD-006.
 - FLUX: TYPE ROL1 per ANSI J-STD-004.

APPLICATION

1. Sleeve will recover to 0.76 (0.030) max.
2. This drawing forms part of Raychem Specification Control Drawing D-711-00.

		300 Constitution Dr Menlo Park, CA 94025, U.S.A.		TITLE: SOLDERSLEEVE, STEPPED INSULATION	
		Raychem Devices		DOCUMENT NO.: D-141-07	
Unless otherwise specified dimensions are in millimeters. [Inches dimensions are shown in brackets]			Tyco Electronics reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.		
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	REV: B		DATE: November 22, 2010	
REVISED BY: UNGUYEN	CAGE CODE: 06090	ECO NUMBER: ECO-10-023873	SCALE: NTS	SIZE: A	SHEET: 1 of 1

© 2001 - 2010 Tyco Electronics Corporation. All rights reserved.
 If this document is printed it becomes uncontrolled. Check for the latest revision.

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)