SPECIFICATION CONTROL DRAWING									55PC0121	
TWO CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, GENERAL PURPOSE, 600 VOLT								Date	1-20-17	Revision E
		This speci	fication sheet form	s a part of the la	atest issue of	Raychem Spec	ification 55PC	D.		
	COMPONENT WIR	2ES - 55PC0111								
				>		\geq				
			CA	BLE CONSTRU	UCTION DET	AILS			7	
			CONDUCTOR SIZE	OUTSIDE DIAMETER			WEIGHT			
		PART NUMBER		(inch)			(lbs/1000 ft.)		_	
		<u>1</u> /	(AWG)	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMI	т	
		55PC0121-30-*	30	.044	.047	.050	1.21	1.29		
		55PC0121-28-*	28	.050	.053	.056	1.69	1.80		
		55PC0121-26-*	26	.058	.061	.064	2.49	2.67		
		55PC0121-24-*	24	.068	.071	.074	3.66	3.85		
		55PC0121-22-*	22	.080	.083	.086	5.44	5.67		
		55PC0121-20-*	20	.097	.099	.101	8.32	8.57		
		55PC0121-18-*	18	.115	.118	.121	12.69	13.14		
		55PC0121-16-*	16	.130	.133	.136	16.21	16.72	_	
		55PC0121-14-*	14	.158	.162	.166	25.08	25.74	_	
		55PC0121-12-*	12	.196	.200	.204	38.80	39.68		
			CABLE RAT	INGS AND ADE	DITIONAL RE	QUIREMENTS				
	TEMPERATURE	RATING: 150°C			1/ PART NI					
Maximum continuous conductor temperature The "*" in the part numbers above shall be replaced by color code										
VOLTAGE RATING: 600 volts (rms) at sea leveldesignators with a slash separating the component wire colors.INSULATION FLAWS:Example: AWG 22, red and blue component wires:										
	Spark Test, 3.0	kV (rms)				55PC012				
	Impulse Dielect	ric Test, 6.0 kV (peak)								
		Users should evaluate the	ne suitability of this pr	oduct for their app	olication. Speci	fications are subj	ect to change w	ithout notice.		
	-	so reserves the right to ma	-			· · · · · · · · · · · · · · · · · · ·				er.
	AN ALTERNATIV	LOR CODE DESIGNATORS S VE COLOR CODE MAY REPL S MAY BE ADDED TO THE PA	ACE MIL-STD-681 COLC	OR CODE DESIGNA	TORS. (EXAMPL	E: "901/902" MAY	' BE REPLACED	BY "Axxx".) OTH	ER CODES	
	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo are trademarks.									Raychem Wire & Cable
Page 1 of 1	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL.									501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-522-6752 Fax: 1-650-361-6297
-	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.									



单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)