

© 1962 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING. APPROVED PER GOVT CONTRACT NO.

REVISIONS				
ZONE	LTR	DESCRIPTION	DATE	APPROVED
✓	W	ECO-08-020973	PY 11-08	JW

LOCATION FOR AMP-TAB FEMALE CONTACT

CAVITY IDENTIFICATION ON P/N (1)582591-1 ONLY

(1)582591-1. SAME AS -1 EXCEPT TO HAVE CAVITY IDENTIFICATION ON TOP SURFACE OF HOUSING

OBSOLETE ~~582591-5~~ 1. SAME AS -1 EXCEPT:
2. WITH FLOATING BUSHINGS (SEE DETAIL "C")

~~582591-1~~ 1. AS SHOWN "J" DIA HOLES = .128

OBSOLETE ~~582591-2~~ 1. SAME AS -1 EXCEPT:
2. "J" DIA HOLES = .156

4. 1. SAME AS -1 EXCEPT; OBSOLETE
2. WITH FLOATING BUSHING. (SEE DETAIL "B")

ALTERNATE MOUNTING EAR CONFIGURATION

RETAINER (2) REQ'D STEEL-CADMIUM PLATED

CLEARANCE FOR #4-40 SCREW

DETAIL "B"

FLOATING BUSHING (2) REQ'D. STAINLESS STEEL, PASSIVATED, FOR -4 ONLY.

CLEARANCE FOR #4-40 SCREW.

(N) ±.003 "J" DIA HOLES

DETAIL "C" -5 ONLY

SECTION A-A

GROOVES FOR "ON CONTACT KEYING" AMP'S OPTION DEPENDING ON METHOD OF MANUFACTURE. FOR "ON CONTACT" KEYING USE KEYING PLUG P/N 583487-1. (MUST BE ORDERED SEPARATELY.)
 MOUNTING EAR CONFIGURATION AMP'S OPTION DEPENDS ON METHOD OF MANUFACTURE.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		CONTRACT NO.		AMP INCORPORATED HARRISBURG, PENNSYLVANIA	
FRACTIONS ±	DECIMALS ±.005	ANGLES ±	DR g. ault	DATE 2-16-66	AMP TRADEMARK
SEE CALLOUT			CHK H. B. ...	DATE 5-67	NAME 31 POSITION AMP-TAB CONNECTOR .100 CENTERS QUAD.
HEAT TREAT			DSGN ENGR	DATE 7-67	
FINISH SEE CALLOUT			APPD J. Kaufman	DATE 7-67	SIZE C
			DSGN APPD	OTHER APPD	CODE IDENT NO 00779
					NUMBER 582591
					REV W
			SCALE 4-		WT. CALC. ACTUAL SHEET

CIRCUIT CAVITY IDENTIFICATION MARKING PER MIL-C-21097

MARK FIRST 5 POSITIONS, NEXT 5 POSITIONS FLAIN

3. LASER MARKING ACCEPTABLE FOR ALL MARKING

AMP INFO
LOC PRINT DIST
DF FO

NUMBER
CUS. 582591

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)