

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	18MAR2017	YC	CW
	B	ECR-21-111798	17SEP2021	WQR	CW

SCALE 3:2

NOTES:

1. TECHNICAL CHARACTERISTICS:

INSULATION MATERIAL: PC

RATED VOLTAGE: 250V

RATED CURRENT: 10A

INSULATION RESISTANCE: $\geq 400M\Omega$

RATED IMPULSE VOLTAGE: 2KV

POLLUTION DEGREE: 3

FLAMMABILITY: UL94V-0

MATING CYCLES: 500 CYCLES

WIRE RANGE: 0.14-2.5 mm² (26-14 AWG)

CONTACT TYPE: CRIMP CONTACT

2. CONTACT NEED TO BE ORDERED SEPARATELY.

(ORDER No. REFER TO DRAWING:T20200X20XX000)

注释:

1. 技术参数:

绝缘材料: PC

额定电压: 250V

额定电流: 10A

绝缘电阻: $\geq 400M\Omega$

额定脉冲电压: 2KV

污染等级: 3

阻燃等级: UL94V-0

插拔次数: 500次

接线范围: 0.14-2.5 mm² (26-14 AWG)

接线类型: 冷压接

2. 端子需要单独订购.

(订货号参考图面: T20200X20XX000)

T2070122201-000	HM-012-F	HM-P12 FEMALE INSERT HM-P12模块母插
PART NUMBER 料号	PART DESCRIPTION 描述	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	18MAR2017	STE TE Connectivity	NAME HM-012-F
		CHK	18MAR2017		
		APVD	18MAR2017		
		PRODUCT SPEC	-		
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	-
		0 PLC	±-	WEIGHT	-
		1 PLC	±-	SIZE	A3
		2 PLC	±-	CAGE CODE	00779
		3 PLC	±-	DRAWING NO	©-T2070122201000
MATERIAL		4 PLC	±-	RESTRICTED TO	-
		ANGLES	±-	SCALE	2:1
		FINISH	-	SHEET	1 OF 1
			-	REV	B
			-	CUSTOMER DRAWING	

1470-19 (3/13)

Downloaded From Oneyc.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)