

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
B	ECR-15-013759		100c+2015	DW	CW
B1	ECR-16-015492		17NOV2016	OY	CW
C	ECR-21-106515		21JUL2021	SQ	CW
C1	ECR-22-158213		29MAY2023	RW	CW

M4 SCREW, RECOMMENDED
TIGHTENING TORQUE 1.2Nm
M4螺丝, 推荐锁紧力矩1.2Nm

4X M3 SCREW, RECOMMENDED
TIGHTENING TORQUE 0.5Nm
4X M3螺丝, 推荐锁紧力矩0.5Nm

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 500V
RATED CURRENT: 16A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 6KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: $0.14mm^2 \sim 4mm^2$ (AWG26-AWG12)
CONTACT TYPE: CRIMP CONTACT
- CONTACTS NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20300X10XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 500V
额定电流: 16A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 6KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: $0.14mm^2 \sim 4mm^2$ (AWG26-AWG12)
接线类型: 冷压接
- 端子需要单独订购。
(订货号参考图面: T20300X10XX000)

TYPE-1, T2040244101-000, TE LOGO
类型-1, T2040244101-000, TE LOGO
TYPE-1, T2040244101-007, TE LOGO
类型-1, T2040244101-007, TE LOGO

PANEL CUT FOR INSERTS FOR USING
WITHOUT HOODS/ HOUSINGS
不使用防护外壳时芯件的安装开孔图

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC \pm
	1 PLC \pm
	2 PLC \pm
	3 PLC \pm
	4 PLC \pm
	ANGLES \pm
MATERIAL	FINISH
-	-

DWN	Gino Yao	19Aug2014
CHK	Chris Wang	19Aug2014
APVD	Xiang Xu	19Aug2014
PRODUCT SPEC	108-137044	
APPLICATION SPEC	114-137044	
WEIGHT	-	
CUSTOMER DRAWING		

NAME		RESTRICTED TO	
HE-024-MC		-	
SIZE	CAGE CODE	DRAWING NO	
A3	00779	T2040244101000	
SCALE		SHEET	REV
1:1		1 OF 2	C1

1470-19 (3/13)

Downloaded From Onevac.com

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
-		SEE SHEET 1	-	-	-

NOTE:
SEE SHEET 1注释:
见页 1

TYPE-2, T2040244101-001, STAINLESS STEEL SCREW, NO LOGO
类型-2, T2040244101-001, 不锈钢螺丝, 无LOGO

T2040244101-001	HE-024-MC	HE-024 MALE INSERT, CRIMPING, STAINLESS STEEL SCREW, NO LOGO HE-024公插, 冷压针, 不锈钢螺丝, 无LOGO	TYPE-2 类型-2
T2040244101-007	HE-024-MC	HE-024 MALE INSERT, CRIMPING HE-024公插, 冷压针	TYPE-1 类型-1
T2040244101-000	HE-024-MC	HE-024 MALE INSERT, CRIMPING HE-024公插, 冷压针	TYPE-1 类型-1
PART NUMBER 料号	PART DESCRIPTION 描述		TYPE 类型

ALL SPEC DIMENSION REFER TO TYPE 1
所有产品规格尺寸参照 TYPE 1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Gino.Yao 19Aug2014	 TE Connectivity	
DIMENSIONS: mm		CHK Chris.Wang 19Aug2014		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD Xiang.Xu 19Aug2014	NAME HE-024-MC	
0 PLC ±-		PRODUCT SPEC 108-137044	SIZE	
1 PLC ±-		APPLICATION SPEC 114-137044	CAGE CODE	
2 PLC ±-		WEIGHT	DRAWING NO	
3 PLC ±-		CUSTOMER DRAWING	RESTRICTED TO	
4 PLC ±-			A300779	
ANGLES ±-			C-T2040244101000	
FINISH			SCALE 1:1	
MATERIAL			SHEET 2 OF 2	
			REV C1	

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)