



REV B DRC26-40S\*-L011

| REVISIONS |                                   |         |          |
|-----------|-----------------------------------|---------|----------|
| SYM       | DESCRIPTION                       | DATE    | APPROVED |
| NC        | NEW RELEASE PER E.O. A14575       | 3-30-34 | J.A.     |
| A         | REVISED PER E.O. A14773           | 12-2-94 | R.D.R.   |
| B         | REDRAWN & REVISED PER E.O. P18865 | 3-31-05 | RDR      |

DRC26-40SA-L011



DRC26-40SB-L011



DRC26-40SC-L011



DRC26-40SD-L011



| CONTACT SIZE | MIN. INSUL. O.D. | MAX. INSUL. O.D. | WIRE RANGE [mm <sup>2</sup> ] REF ONLY |
|--------------|------------------|------------------|--|
| 20           | .040 [1.016]     | .095 [2.413]     | 16-20 AWG [1.0-0.5]                    |

- SEE KEY ORIENTATION
1. DIMENSIONS ARE IN INCHES [mm].
  2. DIMENSION TOLERANCE: ±.025 [ .635]
  3. PLUG IS SUPPLIED WITH DUST CAP (NOT SHOWN).
  4. FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 0425-015-0000.
  5. THIS PLUG MATES WITH DRC23-40P\*-\*\*\*\* RECEPTACLE. (\* = A,B,C,D KEYS; \*\*\*\* = ALL MODIFICATIONS)

6. RECOMMENDED RETAINING BOLT TORQUE: 25-28 IN-LB [2.82-3.16 NM].
7. MATERIAL: HOUSING: PLASTIC (BLACK); BOLT: STAINLESS STEEL; CLIP: STEEL; GROMMET: RUBBER.

|                  |                      |   |  |            |
|------------------|----------------------|---|--|------------|
| SIGNATURE & DATE |                      | PLUG<br>40 CONTACTS, SIZE 20<br>-L011 MOD<br>DRC SERIES | CP   | MATL. CODE |
| DR               | J. APOSTOL 17MAR2005 |   | The Deutsch Company<br>DEUTSCH I.P.D.<br>3850 INDUSTRIAL AVE.<br>HEMET, CALIF. 92545 |            |
| CHK              | R. Meier 3/28/05     |   | B DRC26-40S*-L011  |            |
| PE               | D. Meyer 3/28/05     |   |  |            |
| APPD             | R. Reed 3-31-05      | ENVELOPE  | DWG SIZE   | CODE 11139 |
| SCALE            | NONE                 | WT  | SHEET   OF   |            |

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)