



PC BOARD MOUNTING DIMENSIONS
 CONNECTOR SIDE
 PC BOARD THICKNESS 1.57±0.18 [.062±.007]

- ⚠ CONTACTS: PHOSPHOR BRONZE.
 MOLDED PARTS: POLYESTER, UL 94V-0 RATED, BLACK.
 BRACKET: ZINC.
 BOARDLOCKS: COPPER ALLOY.
- ⚠ CONTACTS: EITHER 0.76 m [.000030] MIN GOLD PLATE FOR A LENGTH OF 3.35 [.132] MIN FROM MATING END OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, 0.76 m [.000030] MIN TOTAL FOR A LENGTH OF 3.35 [.132] MIN FROM MATING END, 3.81 m [.000150] MIN TIN FOR A LENGTH OF 3.23 [.127] MIN FROM OPPOSITE END, BOTH OVER 1.27 m [.000050] MIN NICKEL.
 BRACKET: 3.81 m [.000150] MIN NICKEL OVER 5.08 m [.000200] MIN COPPER.
 BOARDLOCKS: 5.08 m [.000200] MIN TIN OVER 1.27 m [.000050] MIN NICKEL.
- ⚠ POSITION NUMBERS SHOWN FOR REFERENCE ONLY.
- ⚠ ACTUAL HOLE SIZE USED WILL DEPEND ON TRACE ROUTING REQUIREMENTS BETWEEN HOLES AND CONNECTOR PLACEMENT TECHNIQUE.
- ⚠ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINIS

| | | |
|------------|-----------|-------------|
| ⚠ OBSOLETE | TRAY | -5750961-2- |
| | TUBE | 5750961-1 |
| | PACKAGING | PART NUMBER |

| | | | | | |
|--|--------------|--------------------|----------|-------------------------------|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DIN | 02-15-05 | Tyco Electronics Corporation | |
| DIMENSIONS: mm [INCHES] | | A. FERNANDEZ-DOCKS | 02-15-05 | Harrisburg, PA 17105-3608 | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | S. SHUFY | 02-15-05 | NAME | |
| 0 PLC | ± - | M. WALMSLEY | | PRODUCT SPEC | |
| 1 PLC | ± - | 108-1228 | | APPLICATION SPEC | |
| 2 PLC | ± 0.13[.005] | 114-40029 | | RESTRICTED TO | |
| 3 PLC | ± - | A1 00779 | | SCALE 4:1 SHEET 1 OF 1 REV B1 | |
| 4 PLC | ± - | CUSTOMER DRAWING | | SIZE CAGE CODE DRAWING NO | |
| ANGLES | ± - | A1 00779 | | WEIGHT | |
| MATERIAL | FINISH | A1 00779 | | C=5750961 | |

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)