



NOTES:
1. CAPTURED CENTER CONTACT

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₁	SEE ECN 92-0572	11/3/92	AD 11/5/92
01 ₂	REVISED DATA TABLE per ECN 95-0262	6/21/95	S. Mobley
01 ₃	REVISED	DM 3/15/99	Wlog 3/16/99

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING CAP	BRASS PER ASTM-B-16 HALF HARD	NICKEL PLATE PER QQ-N-290
Nominal Impedance (Ohms) 50	Force to Engage: (Lbs) 3.4 MAX	Temperature Rating -65° to +165°C	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
Frequency Range (GHz) DC to 6.0	& Disengage: (Lbs) 1.77 MIN - 4.5 MAX	Vibration MIL-STD-202, Method 204, Condition B	CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
Volt Rating (VRMS MAX) @ Sea Level 335	Center Contact Captivation Axial (Lbs) 4.5 @ 1 minute with .006" Displacement	Thermal Shock MIL-STD-202, Method 107, Condition b	COMPONENT	MATERIAL	FINISH
VSWR 12:1 MAX		Moisture Resistance MIL-STD-202, Method 106	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCE ON DEC ANGLES ±0.13 ° 1°	AMPA Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	
Insertion Loss .1dB MAX/1000 MHz		Corrosion - MIL-STD-202, Method 101, Condition B, 48 Hrs	USE ASSY PROCEDURE	TITLE OSX PRINTED WIRING BOARD RIGHT ANGLE JACK RECEPTACLE STRAIGHT TERMINAL	
Corona, 70,000 Ft (VRMS MIN) 250			NO. AP. N/A	SIZE B	CODE IDENT NO. 26805
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000	XX.XX = mm .XXX = in			SCALE 6:1	5864-5001-10
Contact Resistance (Milliohms MAX) Center Contact 5.0					REV 01 ₃
Outer Contact 1.0					SHEET 1 OF 1
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670					
I.R.(Megohms MIN) 10,000					

CUSTOMER DRAWING

AMP PART # 1061023-1
SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)