

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	11MAY2015	DW	CW
	A1	ECR-17-018349	14DEC2017	DW	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:

CONTACT MATERIAL: BRASS

SURFACE PLATING:

SILVER PLATING:  $\geq 2\mu\text{m}$ CONTACT RESISTANCE:  $\leq 0.5\text{m}\Omega$ WIRE RANGE: 25 mm<sup>2</sup>

OPERATION TEMPERATURE: -40~+125°C

注释:

1. 技术参数:

公针材料: 黄铜

表面电镀:

镀银:  $\geq 2\mu\text{m}$ 接触电阻:  $\leq 0.5\text{m}\Omega$ 接线范围: 25 mm<sup>2</sup>

工作温度: -40~+125°C

T2060001025-000	CHM-25	CHM-25, SILVER PLATING HMN-001公针 25mm <sup>2</sup> , 镀银	25	19
PART NUMBER 料号	PART DESCRIPTION 描述		WIRE GAUGE (mm <sup>2</sup> ) 线规 (mm <sup>2</sup> )	STRIPPING LENGTH (mm) 剥线长度 (mm)
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11MAY2015 David Wang		
DIMENSIONS: mm		CHK 11MAY2015 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 11MAY2015 Xiang Xu		
0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-		PRODUCT SPEC 108-137057		
MATERIAL		APPLICATION SPEC 114-137057	NAME CHM-25 HM PIN CONTACT	RESTRICTED TO
FINISH		WEIGHT	SIZE A3	CAGE CODE 00779
-		Customer Drawing	DRAWING NO T2060001025000	
-		SCALE 2:1	SHEET 1 OF 1	
			REV A1	

1470-19 (3/13)

Downloaded From [Onevac.com](http://Onevac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)