



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION
- DUST COVER INSTALLED FOR SHIPPING.
- KEYING SHOWN IN POSITION "01" FOR REFERENCE ONLY. SEE TABLE FOR KEYING POSITION. FOR POSITION "00" KEYING SHIPPED UNASSEMBLED.
- CONTACTS PACKAGED SEPARATELY AND SHIPPED WITH CONNECTOR.

COMPONENT	MATERIAL	FINISH
SHELL	DIE CAST ALUMINUM PER ASTM-B-85	ELECTROLESS NICKEL PER MIL-C-26074
INSERT RETENTION PLATES	ALUMINUM ALLOY PER ASTM-B-209	ELECTROLESS NICKEL PER MIL-C-26074
SCREWS AND LOCKWASHERS	STEEL OR STAINLESS STEEL	CHROMATE OVER ZINC OR PASSIVATED
POLARIZING KEYS	ZINC ALLOY PER ASTM-B-86	-
POLARIZING KEY RETAINING PLATE	ALUMINUM ALLOY PER ASTM-B-209	BLUE ANODIZED PER MIL-A-8625
INSERTS	THERMOSET OR THERMOPLASTIC PPS PER MIL-M-24519	-
DUST COVER	CONDUCTIVE THERMOPLASTIC	-

"00"	MODULE A 208264-2 (SZ 22 CRIMP SOCKET CONTACT; QTY=150)	1996952-1
	MODULE B 208265-3 (SZ 20 CRIMP PIN CONTACT; QTY=60)	
KEYING POSITION	MODULE C 208265-3 (SZ 20 CRIMP PIN CONTACT; QTY=24)	PART NUMBER
	MODULE D 208268-3 (SZ 16 CRIMP PIN CONTACT; QTY=10)	
	CONTACTS INCLUDED AND NOT INSTALLED	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES (mm)

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± .005
1 PLC	± .004
2 PLC	± .003
3 PLC	± .002
4 PLC	± .001
ANGLES	± .001

MATERIAL: SEE TABLE

FINISH: SEE TABLE

WEIGHT: --

CUSTOMER DRAWING

SCALE: 3:2

SHEET: 1 OF 1

REV: A

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN: C.C.THOMAS 10-3-08, CHK: K.THACKSTON 10-3-08, APVD: K.THACKSTON 10-3-08, NAME: K.THACKSTON, PRODUCT SPEC: RCPT ASSY, SIZE 2, ARINC 600 (150/60/34), RR, APPLICATION SPEC: --, SIZE: A1, CAGE CODE: 00779, DRAWING NO: 1996952, RESTRICTED TO: --

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)