



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REV/REDRAWN/ECN 17976	11/30/87	RW
B	REV/ECN 19297	11/17/89	BSH
03 ₀	ECN 92-0010	08/13/92	<i>JD</i> <i>DePinto</i>

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	COMPONENT	MATERIAL	FINISH
Nominal Impedance (Ohms) <u>50</u> Frequency Range (GHz) DC to <u>4</u> Volt Rating (VRMS MAX) @ Sea Level <u>335</u> VSWR <u>1.10 ±0.16 f(GHz)</u> Insertion Loss (dB MAX) <u>0.30</u> RF Leakage (dB MIN) <u>-55 @ 2-3 GHz</u> Corona, 70,000 Ft (VRMS MIN) <u>250</u> Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,000</u> Contact Resistance (Milliohms MAX) Center Contact <u>6.0</u> Outer Contact <u>2.0</u> Cable to Housing <u>N/A</u> RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>700</u> I.R.(Megohms MIN) <u>1,000</u>	Interface Dimensions MIL-STD-348A, OSM Fig. 310.2 OSMB Fig. 311.2 Recommended Mating Torque <u>N/A</u> Mating Characteristics: Insertion (MAX lbs) OSM <u>3.0</u> OSMB <u>2.5</u> Withdrawal (MIN Oz) OSM <u>1.0</u> OSMB <u>1.0</u> Force to Engage and Disengage (in-lbs MAX) OSM <u>2.0</u> (lbs MAX) OSMB <u>14.0</u> Center Contact Captivation Axial (Lbs) <u>6.0</u> Radial (In-Oz) <u>N/A</u> Cable Retention Axial Force (Lbs) <u>N/A</u> Torque (In-Oz) <u>N/A</u> Weight (Grams) <u>TBD</u>	Temperature Rating <u>-65°C to +125°C</u> Vibration MIL-STD-202, Method 204, Condition B Shock MIL-STD-202, Method 213, Condition B Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 85°C Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	HOUSING SLEEVE DIELECTRIC CENTER CONTACT RETAINING RING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 PTFE FLUOROCARBON PER ASTM-D-1457 BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	PASSIVATE PER QQ-P-35 N/A GOLD PLATE PER MIL-G-45204 GOLD PLATE PER MIL-G-45204
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °		DRAWN BY <u>BSH</u> DATE <u>11/19/87</u> CHECKED BY <u>JW</u> DATE <u>11/24/87</u> APPD BY <u>RW/BC</u> DATE <u>12/2/87</u>		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	
TITLE SMB PLUG TO OSM JACK ADAPTER		USE ASS'Y PROCEDURE NO. AP. <u>N/A</u>		SIZE <u>B</u> CODE IDENT NO. <u>26805</u>	5182-2240-00 REV <u>03₀</u>
SCALE <u>5 : 1</u>		SHEET 1 OF 1			

CUSTOMER DRAWING

AMP PART # 1060498-1
 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)