
## Molded Parts Specification Control Drawing

- 1. All dimensions are in  $\frac{\text{incnes}}{[\text{millimeters}]}; \frac{\text{iso}}{[\text{gms}]}$
- 2. Dimensions appearing in table are as follows:
  - a As Supplied
  - b After Unrestricted Recovery
- 3. Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.

  4. Weight shown in table of dimensions is based on polyolefin part.



AFTER UNRESTRICTED RECOVERY

204A511

Boot, Coax Strain Relief

TABLE OF DIMENSIONS													
PART	н		J		Р	R	w	Weight	This Boot Fits		its		
NUMBER	Min	Мах	Min	Max	±10%	±10%	±20%	Nom	MIL-C-26482	BNC-TNC	RG/U		
	a	b	a	b	b	b	b	b	Shell Size	Connector	Cable		
204A511	.50 [12,7]	.31 [7,9]	.18 [4,6]	.08 [2,0]	1.12	.58 [14,7]	.04 [1,02]	.001 [0,45]	6,8	UG88A/U	196		
				3	2 -9 -13	15 /13	1	1					

**TUCO**/Electronics/Raychem

Revision : C Date: 2/19/02 Part Number : 204A511

Part Number :

Description :


Description: Boot, Coax Strain Relief

Molded Parts Specification Control Drawing

204A511 Part Number :

Description: Boot, Coax Strain Relief

COMPATABILITY CHART										
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION					
-3	Polyolefin, Semi-rigid	RT-301	/42; /86	S-1017;S-1048	Adhesive					
-4	Polyolefin, Flexible	RT-1304	/42; /86	S-1017;S-1048	Adhesive					
-6	Silicone	RT-602	N/A							
-25	Elastomer, Fluid Resistant	RT-1325	/42; /86	S-1017; S-1048	Adhesive					



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

If this document is printed it becomes uncontrolled. Check with the web for latest revision.

## **TUCO**/Electronics/Raychem

TYCO ELECTRONICS 307 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision : C Date: 2/19/02 Part Number : 204A511

Description: Boot, Coax Strain Relief

CAD FILE MP02019

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>TE Connectivity(泰科)