



- 1 FOR USE WITH 2.36 [.093] MINIMUM THICK PRINTED CIRCUIT BOARD. REFER TO APPLICATION SPECIFICATION FOR PRINTED CIRCUIT BOARD LAYOUT DIMENSIONS AND FINISH RECOMMENDATIONS.
- 2 HOUSING: NYLON POLYESTER, UL 94V-0 RATED, GLASS FILLED, BLACK. CONTACTS: COPPER ALLOY. SHELL: CARBON STEEL.
- 3 SHELL: 5.08µm[.000200] MIN TIN OVER 2.54µm[.000100] MIN COPPER.
- 4 CONTACTS:
 0.76 MICRO METERS [.000030] MINIMUM GOLD IN MATING AREA.
 2.54 MICRO METERS [.000100] MINIMUM TIN OR TIN-LEAD ON COMPLIANT PIN. ALL OVER 1.27 MICRO METERS [.000050] MINIMUM NICKEL.
 OR
 GOLD FLASH OVER PALLADIUM NICKEL.
 0.76 MICRO METERS [.000030] MINIMUM TOTAL IN MATING AREA.
 2.54 MICRO METERS [.000100] MINIMUM TIN OR TIN-LEAD ON COMPLIANT PIN. ALL OVER 1.27 MICRO METERS [.000050] MINIMUM NICKEL.
- 5 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.

788458-1
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009.		DIN M. BINNER 02 OCT 98	TE Connectivity
		CHK C. OBERMAN 06 OCT 98	
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD J. OLSON 08 OCT 98	NAME
	0 PLC ± -		PLUG ASSEMBY, SIZE 4, 37 POSITION, MEDIUM PROFILE, ACTION PIN™
	1 PLC ± -		108-40014
	2 PLC ± 0.13 [.005]		FRONT METAL SHELL, AMLIMITE™ HD-20
	3 PLC ± -		APPLICATION SPEC
	4 PLC ± -		114-40026
	ANGLES ± °		SIZE CAGE CODE DRAWING NO RESTRICTED TO
MATERIAL	FINISH	WEIGHT	A1 00779 C=788458
		CUSTOMER DRAWING	SCALE 4:1 SHEET 1 OF 1 REV C

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)