

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00	K	REVISED PER ECO-11-006478	30MAR2011	CJV CWR

0.51 MAX
[.020]

18.59 TYP REF
[.732]

NUMBER INDICATES 26-30 AWG WIRE RANGE

6.40
[.252] MIN REF
LOCALIZED TIN
PLATE AREA

2.54 MIN
[.100]
LOCALIZED GOLD
PLATE AREA

FOR FIT WITH WIRE SIZE
26-30 AWG

SECTION B-B

1 GOLD PLATING PER MIL-G-45204, TIN PLATING PER MIL-T-10727, NICKEL PLATING PER QQ-N-290.

2 0.76 μ m [.000030] MIN GOLD IN LOCALIZED GOLD PLATE AREA, 2.54 μ m [.000100] MIN BRIGHT TIN OR BRIGHT TIN-LEAD IN MIN LOCALIZED TIN PLATE AREA, ALL OVER 0.76 μ m [.000030] MIN NICKEL.

3 GOLD FLASH IN LOCALIZED GOLD PLATE AREA, 2.54 μ m [.000100] MIN BRIGHT TIN OR BRIGHT TIN-LEAD IN MIN LOCALIZED TIN PLATE AREA, ALL OVER 0.76 μ m [.000030] MIN NICKEL.

4. MAX INSULATION OD = .060.

5 0.76 μ m [.000030] MIN GOLD IN LOCALIZED GOLD PLATE AREA, 2.54 μ m [.000100] MIN MATTE TIN IN MIN LOCALIZED TIN PLATE AREA, ALL OVER 0.76 μ m [.000030] MIN NICKEL.

ID ACCOMMODATES
Ø1.016±0.038
[.0400±.0015]
PIN CONTACT

FINISH	PART NUMBER
5	745931-8
3	745931-5
2	745931-3

OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. RICHARD 03/19/90	TE Connectivity	
DIMENSIONS: INCHES		CHK W. LENKER 3-22-90	CONTACT SOCKET, MASS TERMINATION, #26-30, HDE-20, AMPLIMITE	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -	SIZE A2	
0 PLC	± -	PRODUCT SPEC	CAGE CODE 00779	DRAWING NO 745931
1 PLC	± -	APPLICATION SPEC	RESTRICTED TO	
2 PLC	± 0.13 [.005]	SCALE 10:1		
3 PLC	± -	SHEET 1 of 1		
4 PLC	± -	REV K		
ANGLES	± -	CUSTOMER DRAWING		
MATERIAL PHOSPHOR BRONZE PER QQ-B-750	FINISH 1			

1471-9 (3/11)

Downloaded From Onevac.com

745931

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)