

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	39	K2	REVISED PER ECO-11-004820	11MAR11	RK HMR

.030±.010  
 IDENTIFIERS ON ENDS OF HOUSING ARE OPTIONAL AT AMP'S DISCRETION  
 .640  
 .125  
 .075 TYP.

LUG LOCATES THAT SIDE OF CAVITY WHICH CONTAINS THE CONTACT LOCKING LEDGE

.040 REF.

A B C D E F G H J K L M N P Q R S T U V W X Y Z

KEY LOCATIONS (REF ONLY)

L±.015  
 .077 REF.  
 .250 MAX.  
 .156 REF.  
 A SPACES AT .156±.003 = B±.003  
 .120 TYP.

1 TOLERANCE NON CUMULATIVE  
 2 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

2	OBSOLETE	A,C,E,H,K,M,Q,S,U,W,Y	3.900	3.744	24	11	25	-2=87159-4
	OBSOLETE	A,C,E,G,J,L,N,Q,S,U,W,Y	3.744	3.588	23	12	24	2- -3
	OBSOLETE	A,D,G,K,N,R,U,X	3.588	3.432	22	8	23	2- -2
	OBSOLETE	A,C,E,G,J,L,N,Q,S,U,W	3.432	3.276	21	11	22	2- -1
	OBSOLETE	A,D,G,K,N,R,U	3.276	3.120	20	7	21	2- -0
2	OBSOLETE	A,C,E,G,J,L,N,Q,S,U	3.120	2.964	19	10	20	1- -9
	OBSOLETE	B,D,F,J,L,N,Q,S	2.964	2.808	18	8	19	1- -8
	OBSOLETE	A,D,F,J,P,S	2.808	2.652	17	6	18	1- -7
	OBSOLETE	A,D,G,K,N,R	2.652	2.496	16	6	17	1- -6
	OBSOLETE	A,C,E,G,J,L,N,Q	2.496	2.340	15	8	16	1- -5
	OBSOLETE	A,D,G,K,N	2.340	2.184	14	5	15	1- -4
	OBSOLETE	A,C,E,G,J,L,N	2.184	2.028	13	7	14	1- -3
	OBSOLETE	A,C,E,G,J,L	1.872	1.716	11	6	12	1- -2
	OBSOLETE	A,D,G,K	1.716	1.560	10	4	11	1- -1
	OBSOLETE	A,C,E,G,J	1.560	1.404	9	5	10	1- -0
2	OBSOLETE	A,D,G	1.404	1.248	8	3	9	-9
	OBSOLETE	A,C,E,G	1.248	1.092	7	4	8	-8
	OBSOLETE	A,C,E	1.092	.936	6	3	7	-7
	OBSOLETE	A,C,E	.936	.780	5	3	6	-6
	OBSOLETE	A,C	.624	.468	3	2	4	-5
	OBSOLETE	A	.468	.312	2	1	3	-4
	OBSOLETE	A	.312	.156	1	1	2	-3
	OBSOLETE	A,D,J,M,	2.028	1.872	12	4	13	-2
	OBSOLETE	A,D	.780	.624	4	2	5	87159-1
			KEY LOCATIONS	L	B	A	NO OF KEYS	NO OF POS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	S. SHUEY	8-7-93		TE Connectivity		
DIMENSIONS: INCHES		CHK	S. SHUEY	8-7-93		HOUSING, MOD I, .156 CL. SINGLE ROW, CRIMP SNAP IN, KEYED		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	S. SHUEY	8-7-93		NAME	108-25016	
0 PLC ± -		PRODUCT SPEC	114-25000			SIZE	CAGE CODE	DRAWING NO
1 PLC ± -		APPLICATION SPEC	WEIGHT		A2	00779	C=87159	
2 PLC ± -		FINISH	CUSTOMER DRAWING		SCALE	4:1	SHEET 1 OF 1	
3 PLC ± .005					RESTRICTED TO	-		
4 PLC ± -					REV	K2		
ANGLES ± -								
MATERIAL: FLAME RETARDANT THERMOPLASTIC COLOR-BLACK								

1471-9 (3/11)

Downloaded From [Onevac.com](http://Onevac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)