



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION
- KEYING SHOWN IN POSITION "01" FOR REFERENCE ONLY. SEE TABLE FOR KEYING POSITION. FOR POSITION "00" KEYING SHIPPED UNASSEMBLED.

COMPONENT	MATERIAL	FINISH
SHELL	DIE CAST ALUMINUM PER ASTM-B-85	ELECTROLESS NICKEL PER MIL-C-26074 CLASS 3 OR 4, GRADE B
RETENTION PLATES	ALUMINUM ALLOY PER ASTM-B-209	ELECTROLESS NICKEL PER MIL-C-26074 CLASS 3 OR 4, GRADE B
SCREWS AND LOCKWASHERS	STAINLESS STEEL	PASSIVATED
POLARIZING POSTS	ZINC ALLOY PER ASTM-B-86	ELECTROLESS NICKEL PER MIL-C-26074 CLASS 4, GRADE B
85 POSN INSERT	THERMOSET	-
11Q11 & 10T10 INSERTS	ALUMINUM ALLOY PER ASTM-B-209	ELECTROLESS NICKEL PER MIL-C-26074 CLASS 3 OR 4, GRADE B
POLARIZING POST RETAINING PLATE	ALUMINUM ALLOY PER ASTM-B-209	BLUE ANODIZED PER MIL-A-8625
FILLER PLUGS	ALUMINUM ALLOY PER ASTM-B-211	ELECTROLESS NICKEL PER MIL-C-26074,

192	MODULE A: - MODULE B: - MODULE C: SIZE 22: 208262-3 (QTY=80) SIZE 16: 208270-2 (QTY=1) SIZE 20: 208267-2 (QTY=4)	1883406-2
OBSOLETE	MODULE A: SIZE 8 QUADRAX: 1445693-1 (QTY=4) SIZE 8 FILLER PLUG: 448545-3 (QTY=7) MODULE B: SIZE 8 COAX (RG-316): 1218820-1 (QTY=8) SIZE 8 FILLER PLUG: 448545-3 (QTY=2) MODULE C: SIZE 22: 208262-3 (QTY=80) SIZE 16: 208270-2 (QTY=1) SIZE 20: 208267-2 (QTY=4)	1883406-1
KEYING POSITION	CONTACTS & FILLER PLUGS INCLUDED NOT INSTALLED	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN: C.C.THOMAS 4-21-06. CHK: K.HOGAN 4-21-06. APVD: K.HOGAN 4-21-06. NAME: PLUG ASSY, SIZE 2, ARINC 600, (11Q11/10T10/85 RR). DIMENSIONS: INCHES/mm. TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± .005, 1 PLC ± .005, 2 PLC ± .005, 3 PLC ± .005, 4 PLC ± .005. MATERIAL: SEE TABLE. FINISH: SEE TABLE. WEIGHT: -. SIZE: A1. CASE CODE: 00779. DRAWING NO: 1883406. CUSTOMER DRAWING. SCALE: 1:1. SHEET: 1 OF 1. REV: C.

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)