



NOTE:

- 1 MATERIAL:  
HOUSING: 30% GLASS FILLED PBT, THERMOPLASTIC, BLACK.  
CONTACT: PHOS BRONZE
- 2 FINISH: CONTACT PLATING TIN (LEAD FREE); 60 UIN MIN. OVER 30 UIN NI  
SOLDERABILITY :95% COVERAGE MIN.;  
WORKING CONDITION:230°±5°C MAX
- 3. MECHANICAL SPECS:  
DURABILITY: 50 CYCLES MIN.  
INSERTION FORCE:300 GRAMS MAX.  
WITHDRAWAL FORCE: 20 GRAMS MIN.  
CONTACT RETENTION: 500 GRAMS MIN.  
ACCEPTS: 0.20-0.30 [.008-.012] LEADS
- 4. ELECTRICAL SPECS:  
VOLTAGE RATING: 250V AC,DC  
CONTACT RESISTANCE: 20 MILLOHMS MAX.  
CURRENT RATING: 1 AMPERE AC,DC  
INSULATION RESISTANCE: 1000 MEGOHMS MIN.  
DIELECTRIC WITHSTANDING VOLTAGE: AC 1000 V MIN.
- 5. OPERATING TEMPERATURE: -40°C TO +105°C
- 6 TE LOGO

△	32	38.10	40.64	1-2199300-2
FINISH	POS	B±0.15	A±0.20	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN WINNG WANG 18NOV2013		TE Connectivity	
DIMENSIONS: mm		CHK SIMON LI 18NOV2013			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD COREL WANG 18NOV2013		NAME	
0 PLC ± -		PRODUCT SPEC		DIP SOCKET, 15.24 CENTERLINE OTC STYLE	
1 PLC ± -		APPLICATION SPEC		SIZE	
2 PLC ± 0.2[.008]		WEIGHT		CAGE CODE	
3 PLC ± -		A1		DRAWING NO	
4 PLC ± -		00779		2199300	
ANGLES ± -		CUSTOMER DRAWING		RESTRICTED TO	
MATERIAL △1		SCALE 5:1		SHEET 1 OF 1	
FINISH △2, △7		REV A			

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)