SPECIFICATION CONTROL DRAWING				7530A181
CHEMINAX 75 OHM, AWG 30, 7 S ⁻			Date	4-30-07
		TRANDS OF 38 AWG, COAXIAL CABLE	Revision	A
THIS SPECIF	FICATION SHEET FORMS A PAR	RT OF THE LATEST ISSUE OF RAYCHEM S	PECIFICATION	1200.
CONSTRUCTION DETAILS		ELECTRICAL CH	CHARACTERISTICS	
	S IN INCHES UNLESS OTHERWISE			
SIGNATED.		CHARACTERISTIC IMPEDANCE	75 ± 3 ohms,	Method B
		CAPACITANCE	17.5 pF/ft. (no	ominal)
A		VELOCITY OF PROPAGATION	77% (nominal)
	CONDUCTOR			
)127	AWG 30, 7 strands of AWG 38, Tin-Coated			
	Copper Clad Steel	ADDITIONAL REQUIREMENTS		
		ELECTRICAL		
)54				00 # (******
	Rayfoam* L Color - Natural	CONDUCTOR RESISTANCE		00 ft. (nominal)
		INSULATION RESISTANCE	for 1000 ft.	nms (minimum)
		JACKET FLAWS		
	SHIELD	SPARK TEST	1.0 kV (rms)	
	AWG 38 Tin-Coated Copper	IMPULSE TEST	6.0 kV (peak)	
		VOLTAGE WITHSTAND (DIELECTRIC)	1000 volts (rn	ns) (minimum)
		ENVIRONMENTAL		
		FLAMMABILITY	Method B	
		HEAT SHOCK	225°C	
		LOW TEMPERATURE-COLD BEND	-30°C/2.75 ind	ch mandrel
	JACKET	VOLTAGE WITHSTAND	1000 volts (rms) (minimum)	
	Zerohal*	(Post Environmental)	1000 voits (11	15) (I'iii'iii'iui'i)
		PHYSICAL		
		INSULATION (DIELECTRIC)		
		ELONGATION	50% (minimu	m)
		TENSILE STRENGTH	1000 lbf/in ² (n	ninimum)
		JACKET		
		ELONGATION	150% (minim	um)
		TENSILE STRENGTH	1200 lbf/in ² (minimum)	
* is a trademark of Tyco Electronics Corporation.		JACKET THICKNESS	.013 inch (nominal)	
Outer jacket color will be black (designated by a "-0" appended to the part number, e.g. 7530A1817-0) unless otherwise specified.		SHIELD COVERAGE	90% (minimu	m)
	th a dash number in accordance			
vith MIL-STD-681. Other codes he part number, as necessary,	s and suffixes may be added to to to capture any additional			
requirements imposed by the p		WEIGHT	6.7 lbs/1000 f	

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.



 Raychem Wire & Cable

 501 Oakside Avenue

 Redwood City, California 94063-3800

 1-800-227-8816
 Fax: 1-650-361-6297

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)