



METPRIG
DIMENSIONS LISTED IN mm [INCHES]

AMP WIRE RANGE	E13288 Listed
22-16 AWG STRANDED	22-16 AWG STRANDED
LR7189 Certified	MILITARY P/N AND CLASS
NOT CERTIFIED	NOT APPLICABLE

△ STAMP AMP 22-18* APPROX AS SHOWN
22-16 TERMINALS ARE STAMPED 22-18 IN
ACCORDANCE WITH MILITARY SPECIFICATION
MIL-T-7928, COMMERCIAL WIRE RANGE IS 22-16

AMP INCORPORATED
CUSTOMER SERVICE SYSTEMS

FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752	VOLTAGE RATING: NOT APPLICABLE	MAX RECOMMENDED OPERATING TEMPERATURE: 170°C MAX
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111	WIRE CROSS SECTIONAL AREA RANGE: 0.26-1.65mm ² [509-3,260] CIR MILS STRANDED	DO NOT SCALE PRINT. DIMENSIONS SPECIFIED IN CHANGES—TOLERANCES ON 1 2 PLC DEC ± 3 ANGLES MATERIAL
FOR ORDER ENTRY	1-800-526-5142	FINISH TIN PLATE 0.00254(.000100) MIN THK PER MIL-T-10727	DR 3-2-93 TA BRINKMAN CHK 3-2-93 DA PATTERSON APPD 3-2-93 DE MILLER APPD 3-2-93 JL HECKLEY PRODUCT SPEC

AMP INCORPORATED
Harrisburg, PA 17105-3508

TERMINAL, FLANGED
SPADE, BUDGET

AMP 1071-6 REV 3-92	328522	PART NO
29-FEB-94 15:11:37	00779	SIZE CASE CODE DRAWING NO
FILED/depot/1123/dwg/123/y. bnd/rev/1. 22-16	10:1	SCALE
	1 OF 1	SHEET

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)