



SOCKET CONTACT, SIZE 22, 62 REQD.
 BODY-MATL: BERYLLIUM COPPER PER QQ-C-530
 FINISH: PLATED GOLD .000050 MIN. THK.
 PER MIL-G-45204 OVER NICKEL .000050 MIN.
 THK. PER QQ-N-290
 HOOD-MAT'L: STAINLESS STEEL PER QQ-S-766
 FINISH: PASSIVATED PER QQ-P-35B

SHELL, FRONT
 MATL: STEEL PER ASTM-A-109
 FINISH: PLATED CADMIUM PER
 QQ-P-416

SHELL, REAR
 MATL: STEEL PER ASTM-A-109
 FINISH: PLATED ZINC PER
 ASTM-B-633, YELLOW CHROMATE

INSERT ASSEMBLY
 MATL: GLASS FIBER REINF.
 FLM. RTD. DIALLYL PHTHALATE
 COLOR: BLUE
 OR POLYPHENYLENE SULFIDE(PPS)
 PER MIL-M-24519, TYPE GST-40F
 COLOR: BLACK

1. THIS RECEPTACLE WILL MATE WITH ANY 62 POSN., SIZE 4 PLUG IN AMPLIMITE SERIES.
2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS RECEPTACLE IS .054 DIA.
3. SST RETENTION CLIPS ARE INCLUDED IN INSERTS.

- ④ PACKAGE STAMPED M24308/2-490F & AMP P/N 211539-1
- ⑤ PACKAGE STAMPED M24308/2-350F & AMP P/N 211539-2
- ⑥ PACKAGE STAMPED M24308/2-361F & AMP P/N 211539-3
- ⑦ AMP P/N 204351-1; MIL P/N 57-354, INCLUDED IN KIT
- ⑧ AMP P/N 91067-1; MIL P/N M81969/1-04
- ⑨ CONNECTOR SUPPLIED WITHOUT CONTACTS; SHOWN FOR ILLUSTRATION ONLY.
- ⑩ UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL

SUPSD BY 204542-2 & 91067-1	SAME AS -1 EXCEPT: ⑥ ⑦ ⑧	211539-3
	SAME AS -1 EXCEPT: ⑤ ⑦	211539-2
	AS SHOWN ④ ⑨	211539-1

THIS DRAWING IS A CONTROLLED DOCUMENT		Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0. PLC ± - 1. PLC ± - 2. PLC ± - 3. PLC ± .005 4. PLC ± - ANGLES ± -	PRODUCT SPEC	NAME RECEPTACLE ASS'Y., AMPLIMITE, 62 POSN., SIZE 4, SERIES 90, W/DUAL FLOAT BUSHINGS
MATERIAL SEE CALLOUT	FINISH SEE CALLOUT	WEIGHT	SIZE A1
CUSTOMER DRAWING		SCALE NTS	SHEET 1 OF 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)