

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	14APR2015	DW	CW
	B	ECR-15-018270	09DEC2015	DW	CW
	B1	ECR-16-006849	13MAY2016	RL	CW
	C	ECR-21-111798	28SEP2021	WQR	CW

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 250V  
RATED CURRENT: 10A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 4KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
OPERATION TEMPERATURE:  $-40\sim+125^{\circ}C$   
WIRE RANGE:  $0.14\sim 2.5\text{ mm}^2$  (26~14 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20200X10XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 250V  
额定电流: 10A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 4KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
工作温度:  $-40\sim+125^{\circ}C$   
接线范围:  $0.14\sim 2.5\text{ mm}^2$  (26~14 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20200X10XX000)


T2111122101-000 SHOWN,  
带 LOGO, 产品型号, 认证标示





T2111122101-001 SHOWN, ALL DIMENSIONS ARE  
SAME AS T2111122101-000, EXCEPT WITHOUT LOGO,  
TYPE DESCRIPTION, TUV AND CUL MARK  
不带 LOGO, 产品型号和认证标示

T2111122101-001	HMN-012-M WITHOUT LOGO HMN-012模块公插 不带LOGO, 产品型号和认证标示
T2111122101-000	HMN-012-M WITH LOGO HMN-012模块公插
PART NUMBER 料号	PART DESCRIPTION 描述

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	14APR2015	 TE Connectivity	
DIMENSIONS: mm		CHK	14APR2015		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	14APR2015		
0 PLC $\pm$ - 1 PLC $\pm$ - 2 PLC $\pm$ - 3 PLC $\pm$ - 4 PLC $\pm$ - ANGLES $\pm$ -		NAME	HMN-012-M		
MATERIAL		PRODUCT SPEC	108-137121	SIZE	A3
FINISH		APPLICATION SPEC	114-137121	CAGE CODE	00779
		WEIGHT	-	DRAWING NO	T2111122101000
		Customer Drawing		RESTRICTED TO	-
		SCALE	1:1	SHEET	1 OF 1
		REV	C		

1470-19 (3/13)

Downloaded From [Oneyac.com](http://Oneyac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)