



RECOMMENDED MOUNTING HOLE PATTERN
 FOR 1.57 THICK P.C. BOARD

3.81	.150		
2.54	.100	44.32	1.745
2.03	.080	33.78	1.330
1.91	.075	26.67	1.050
1.57	.062	19.05	.750
1.52	.060	17.27	.680
1.27	.050	12.83	.505
0.25	.010	12.70	.500
0.13	.005	9.14	.360
0.08	.003	7.37	.290
0.00127	.000050	6.35	.250
0.000762	.000030	4.06	.160
MM	IN	MM	IN

CONVERSION TABLE

- 1 PARTS COMPLY WITH AMP SOLDERABILITY SPECIFICATION 109-11-5.
- 2 0.00076 GOLD OVER 0.00127 MIN NICKEL WITH MATTE TIN LEAD ON SOLDER TAIL.
- 3 CIRCUIT IDENTIFICATION CHARACTERS ARE ADJACENT TO THE INDICATED CAMMIES BUT LOCATION AND ORIENTATION MAY DIFFER FROM PRINT.
- 4 0.00076 GOLD OVER 0.00127 MIN NICKEL WITH MATTE TIN ON SOLDER TAIL.
- 5 SUPERSEDED BY 3-643230-0
- 6 DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY CONDITION. ADDITIONAL 2% GROWTH DUE TO END USE LOCATION MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR

PH BRZ.	△	NYLON UL 94V-0	3-643230-0
PH BRZ.	△	NYLON UL 94V-0	643230-2
PH BRZ.TIN		NYLON UL 94V-0	643230-1
CONTACT		HOUSING	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT
 CONTROLLED BY: WILKINER 2398883
 CONTROLLED BY: RIBOILL 2398883
 CONTROLLED BY: SOKET HEADER ASSEMBLY, RIGHT ANGLE MOUNT (A POSITION), UNIVERSAL, MAT-N-(A-10KTM)
 PART NUMBER: 643230
 DATE: 10/07/79
 DRAWN BY: C-643230
 CHECKED BY: 4:1
 DATE: 1
 REV: 3

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)