

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER ECR-18-002379	27FEB2018	BW	MD
	A2	REVISED PER ECR-20-002859	17MAR2020	BKW	SW
	A3	REVISED PER ECR-20-100299	10AUG2020	BDA	WW
	A4	ECR-23-187950	26SEP2023	SP	FL

NOTES:

- CONTINUOUS STRIP ON REELS
- REFERENCE CRIMP INFORMATION:
WIRE RANGE - 18 TO 14AWG OR TWO 18AWG WIRES
INSULATION RANGE - 2.3 TO 3.4MM,
FOR DUAL 18AWG WIRE, 1.9MM MAX INSULATION DIAMETER EACH
WIRE BARREL - .110 INCH CRIMP WIDTH, F TYPE
INSULATION BARREL - .180 INCH CRIMP WIDTH, F TYPE
- RECOMMENDED MATING TAB:
TAB WIDTH 6.3 ± 0.1 MM, THICKNESS 0.8 ± 0.03 MM
HOLE DIAMETER 1.7MM, CENTER LOCATED 2.5MM FROM TIP

△ DIFFERENT MARKING PART NUMBER

SECTION F - F

SECTION J - J

SECTION G - G
SCALE 8:1

SECTION H - H
SCALE 8:1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL
BRASSTOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±1.00
1 PLC ±0.50
2 PLC ±0.25
3 PLC ±
4 PLC ±
ANGLES ±
FINISH SEE TABLEDWN 06DEC2016
J. POTERJOYCHK 06DEC2016
F. LUPOAPVD 06DEC2016
R. ROBONEPRODUCT SPEC
108-143029APPLICATION SPEC
114-2074WEIGHT
-

CUSTOMER DRAWING

NAME
RECEPTACLE, POSITIVE-LOCK,
RAST 6.35 SERIES

SIZE A3 CAGE CODE - DRAWING NO C-2238135 RESTRICTED TO -

SCALE 5:1 SHEET 1 OF 1 REV A4

TIN	BRASS	2238135-4 △4
TIN	BRASS	2238135-2
PLAIN BRASS	BRASS	2238135-1
FINISH	MATERIAL	PART NO

TE Connectivity

SCALE 5:1 SHEET 1 OF 1 REV A4

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)