



- 1 AMP, CSA, and DATE CODE with .062 ±0.015 HIGH CHARACTERS WHERE SIZE PERMITS.
- 2 HOUSING: 1-70 POSITION SIZES MAY BE PPS, GLASS-FILLED OR PCT, GLASS-FILLED. POSITION SIZES GREATER THAN 70 WILL BE PPS, GLASS-FILLED.
- 3 CONTACT: PHOSPHOR BRONZE.
- 4 CONTACT FINISH: DUPLEX PLATED 0.00038 [.000015] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] BRIGHT TIN-LEAD ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 5 THESE DIMENSIONS PERTAIN TO CAVITY Ø'S ONLY, NOT TO CONTACT LOCATIONS.
- 6 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE CONTACT BEAMS).
- 7 CSA LOGO INK STAMPED WHITE ON HOUSING.
- 8 CONTACT FINISH: DUPLEX PLATED 0.00038 [.000015] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] MATTE TIN ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 9 ROHS 2002/95/EC COMPLIANT.
- 10 RECESSED AREA AROUND MOLD GATE IS OPTIONAL. THIS FEATURE IS ALLOWABLE ON EITHER SIDE OF HOUSING OR MAY NOT BE PRESENT AT ALL.
- 11 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	8	1, 2, 7, 8	1, 2, 7, 8	26.87 [1.058]	7	16	6-534975-5
		1, 2, 39, 40	1, 2, 39, 40	108.15 [4.258]	39	80	6-534975-4
		1, 2, 34, 35	1, 2, 34, 35	95.45 [3.758]	34	70	6-534975-3
		1, 2, 29, 30	1, 2, 29, 30	82.75 [3.258]	29	60	6-534975-2
		1, 2, 24, 25	1, 2, 24, 25	70.05 [2.758]	24	50	6-534975-1
		1, 2, 19, 20	1, 2, 19, 20	57.35 [2.258]	19	40	6-534975-0
		1, 2, 17, 18	1, 2, 17, 18	52.27 [2.058]	17	36	6-534975-9
		1, 2, 14, 15	1, 2, 14, 15	44.65 [1.758]	14	30	6-534975-8
		1, 2, 11, 12	1, 2, 11, 12	37.03 [1.458]	11	24	6-534975-7
		1, 2, 9, 10	1, 2, 9, 10	31.95 [1.258]	9	20	6-534975-6
OBSOLETE	4	1, 2, 5, 6	1, 2, 5, 6	21.79 [.858]	5	12	6-534975-5
		1, 2, 50, 51, 99, 100	1, 2, 50, 51, 99, 100	260.55 [10.258]	99	200	6-534975-4
		1, 2, 40, 41, 79, 80	1, 2, 40, 41, 79, 80	209.75 [8.258]	79	160	6-534975-3
		1, 2, 30, 31, 59, 60	1, 2, 30, 31, 59, 60	158.95 [6.258]	59	120	6-534975-2
		1, 2, 24, 25, 49, 50	1, 2, 24, 25, 49, 50	133.55 [5.258]	49	100	6-534975-1
		1, 2, 7, 8	1, 2, 7, 8	26.87 [1.058]	7	16	1-534975-5
		1, 2, 39, 40	1, 2, 39, 40	108.15 [4.258]	39	80	1-534975-4
		1, 2, 34, 35	1, 2, 34, 35	95.45 [3.758]	34	70	1-534975-3
		1, 2, 29, 30	1, 2, 29, 30	82.75 [3.258]	29	60	1-534975-2
		1, 2, 24, 25	1, 2, 24, 25	70.05 [2.758]	24	50	1-534975-1
OBSOLETE	4	1, 2, 19, 20	1, 2, 19, 20	57.35 [2.258]	19	40	1-534975-0
		1, 2, 17, 18	1, 2, 17, 18	52.27 [2.058]	17	36	534975-9
		1, 2, 14, 15	1, 2, 14, 15	44.65 [1.758]	14	30	534975-8
		1, 2, 11, 12	1, 2, 11, 12	37.03 [1.458]	11	24	534975-7
		1, 2, 9, 10	1, 2, 9, 10	31.95 [1.258]	9	20	534975-6
		1, 2, 5, 6	1, 2, 5, 6	21.79 [.858]	5	12	534975-5
		1, 2, 50, 51, 99, 100	1, 2, 50, 51, 99, 100	260.55 [10.258]	99	200	534975-4
		1, 2, 40, 41, 79, 80	1, 2, 40, 41, 79, 80	209.75 [8.258]	79	160	534975-3
		1, 2, 30, 31, 59, 60	1, 2, 30, 31, 59, 60	158.95 [6.258]	59	120	534975-2
		1, 2, 24, 25, 49, 50	1, 2, 24, 25, 49, 50	133.55 [5.258]	49	100	534975-1
FINISH	ROW M	ROW N	B	A	NO OF POSN	PART NUMBER	
POSITION WITH BOARD RETENTION							

11 SUPERSEDED BY 5-534975-8

11 OBSOLETE

11 SUPERSEDED BY 5-534975-2

11 OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT. **STE** TE Connectivity

APVD: DOUG SARVER

PRODUCT SPEC: RECEPTACLE ASSY, MOD II, DBL ROW, 2.54 X 2.54 [.100 X .100] CL.

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 534975

SCALE: 6:1 SHEET: 1 OF 1 REV: S4

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)