



| REVISIONS |             |         |             |
|-----------|-------------|---------|-------------|
| REV       | DESCRIPTION | DATE    | APPROVED    |
| 01        | REVISED     | 9/21/95 | DCm 5/21/96 |

| ELECTRICAL                                                          | MECHANICAL                                            | ENVIRONMENTAL                                                   | HOUSING                                                                                                                                                                                                         | MATERIAL                                                                        | FINISH                                                                 |
|---------------------------------------------------------------------|-------------------------------------------------------|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|------------------------------------------------------------------------|
| Nominal Impedance (Ohms) <u>50</u>                                  | Interface Dimensions MIL-STD-348A, Fig. 310.2         | Temperature Rating <u>-65°C to +125°C</u>                       | DIELECTRIC                                                                                                                                                                                                      | STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303                           | GOLD PLATE PER MIL-G-45204                                             |
| Frequency Range (GHz) DC to <u>12.4</u>                             | Recommended Mating                                    | Vibration MIL-STD-202, Method 204, Condition B.                 | CENTER CONTACT                                                                                                                                                                                                  | TFE FLUOROCARBON PER ASTM-D-1457                                                | N/A                                                                    |
| Volt Rating (VRMS MAX) @ Sea Level <u>335</u>                       | Torque <u>7-10 in-lbs.</u>                            | Shock MIL-STD-202, Method 213, Condition I.                     |                                                                                                                                                                                                                 | BERYLLIUM COPPER PER ASTM B 196 OR ASTM B-197 ALLOY C17300, CONDITION H         | GOLD PLATE PER MIL-G-45204                                             |
| VSWR <u>N/A</u>                                                     | Mating Characteristics:                               | Thermal Shock MIL-STD-202, Method 107B, Condition B             | COMPONENT                                                                                                                                                                                                       |                                                                                 |                                                                        |
| Insertion Loss (dB MAX) <u>N/A</u>                                  | Insertion (MAX Lbs) <u>3.0</u>                        | Moisture Resistance MIL-STD-202, Method 106                     | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON                                                                                                                                                | DRAWN BY <u>BWG</u> DATE <u>3/11/68</u>                                         | <b>AMP Incorporated</b><br>140 Fourth Avenue<br>Waltham, MA 02451-7599 |
| RF Leakage (dB MIN) <u>N/A</u>                                      | Withdrawal (MIN Oz) <u>1.0</u>                        | Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray | FRAC. DEC. ANGLES                                                                                                                                                                                               | CHECKED BY <u>PRB</u> DATE <u>3/11/68</u>                                       |                                                                        |
| Corona, 70,000 Ft (VRMS MIN) <u>250</u>                             | Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u> |                                                                 | ± 1/64 ±.005 ± °                                                                                                                                                                                                | APPD BY <u>DN</u> DATE <u>4/5/68</u>                                            |                                                                        |
| Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,000</u> | Center Contact Captivation                            |                                                                 | These drawings and specifications are the property of M/A-COM and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission. | <b>AMP</b><br>TITLE <u>OSM FLANGE MOUNT JACK RECEPTACLE SOLDER POT TERMINAL</u> |                                                                        |
| Contact Resistance (Milliohms MAX)                                  | Axial (Lbs) <u>6.0</u>                                |                                                                 |                                                                                                                                                                                                                 | .XXX = in                                                                       | SIZE <u>B</u> CODE IDENT NO. <u>26805</u> 2052-5085-00 REV <u>01</u>   |
| Center Contact <u>3.0</u>                                           | Radial (In-Oz) <u>4.0</u>                             |                                                                 |                                                                                                                                                                                                                 | XX.X = mm                                                                       | SCALE <u>4:1</u> SHEET 1 OF 1                                          |
| Outer Contact <u>2.0</u>                                            | Cable Retention                                       |                                                                 |                                                                                                                                                                                                                 |                                                                                 |                                                                        |
| Cable to Housing <u>N/A</u>                                         | Axial Force (Lbs) <u>N/A</u>                          |                                                                 |                                                                                                                                                                                                                 |                                                                                 |                                                                        |
| RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>         | Torque (In-Oz) <u>N/A</u>                             |                                                                 |                                                                                                                                                                                                                 |                                                                                 |                                                                        |
| LR.(Megohms MIN) <u>10,000</u>                                      | Weight (Grams) <u>TBD</u>                             |                                                                 |                                                                                                                                                                                                                 |                                                                                 |                                                                        |

CUSTOMER DRAWING AMP PART # 1052873-1 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)