

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
B2		REVISED PER ECO-13-009966	18JUN2013	DD DS
B3		REVISED PER ECO-15-007694	21MAY2015	DD DS

(25.2)

(R8.00-8.60)

1 MATERIAL: PBT, 15% GLASS FILLED, COLOR: BLACK

2. ACCEPTS #4 SELF TAPPING SCREW (ELCO HI-LO THREAD CUTTING STYLE OR EQUIVALENT) TO BE DRIVEN AT 0.6 ± 0.2 N-M FOR INITIAL ASSEMBLY.

3 MATERIAL: PBT, 17% GLASS FILLED, UL RATED V-0/5VA, COLOR: GRAY

(7.00)

(Ø2.40)

(47.1)

(Ø3.40)

(38.0)

SECTION B-B

SCALE 1:1

3	776464-2
1	776464-1
MATERIAL	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. VESTAL 02APR2003	TE Connectivity	
DIMENSIONS: mm		CHK M. TRULL 02APR2003		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. TRULL 02APR2003	NAME WIRE RELIEF, 23 POSITION	
0 PLC ±-		PRODUCT SPEC	SIZE CAGE CODE DRAWING NO RESTRICTED TO	
1 PLC ±-		APPLICATION SPEC	A200779 C-776464	
2 PLC ±0.10		WEIGHT	SCALE 2:1 SHEET 1 OF 1 REV B3	
3 PLC ±-		CUSTOMER DRAWING		
4 PLC ±-				
ANGLES ±2°				
FINISH				
MATERIAL SEE NOTES				

1471-9 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)