

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
FT	8	P	LTR	DESCRIPTION	DATE	DWN	APVD
			AV1	REVISED PER ECO-13-008672	31AUG2013	KH	DR

- △1 DIALLYL PHTHALATE, BLUE.
- △2 STAINLESS STEEL.
- △3 STEEL, NICKEL PLATED.
- △4 ALUMINUM, IRIDITE.
- △5 PHENOLIC, BLACK.
- △6 ALUMINUM, ANODIZED.
- △7 OBSOLETE PART NO.

OBSOLETE									
△7	△7	△7	△7	△7	△7				
-	-	-	-	-	1	200867-1	△2	JACKSCREW ASSY, FEMALE, LONG	22
1	-	-	-	-	-	200517-1	△6	180° SHIELD, 2 PIECE	21
-	2	2	-	-	-	200330-2		#4-40 SCREW	20
-	2	2	-	-	-	200773-2		#4-40 NUT	19
-	2	2	-	-	-	200503-1		#4 LOCKWASHER	18
-	-	-	1	-	-	201350-2	△4	PIN HOOD EXTERNAL	17
-	-	-	-	1	-	204814-1		GROUNDING CONNECTOR - 34 POSN	16
-	-	-	-	1	-	4-202430-5		ASSEMBLED KIT - 34 POSN	15
-	-	-	-	-	34	66105-1		CONTACT ASSY SOCKET	14
-	-	2	2	-	-	200835-2	△2	CONTACT SOCKET CORNER	13
-	-	2	2	-	-	200833-2	△2	CONTACT PIN CORNER	12
-	1	1	-	-	-	201224-1	△3	STRAIN RELIEF ASSY	11
-	-	-	-	-	1	201846-1	△3	STRAIN RELIEF ASSY, LONG	10
1	-	-	-	-	-	201413-1	△2	JACKSCREW ASSY MALE, LONG	9
1	-	-	-	-	-	201414-1	△2	JACKSCREW ASSY FEMALE, LONG	8
-	2	-	-	-	-	203535-2		JACKSCREW SPECIAL	7
-	-	1	1	-	-	200874-1	△2	FIXED JACKSCREW ASSY, MALE	6
-	-	1	1	-	-	200875-1	△2	FIXED JACKSCREW ASSY, FEMALE	5
-	-	-	-	-	1	200871-1	△2	JACKSCREW ASSY, LONG	4
1	-	-	-	-	-	201357-1	△5	BLOCK	3
-	1	1	-	-	1	200838-2	△5	BLOCK FEMALE	2
-	-	-	1	-	-	201357-3	△1	BLOCK, MALE, DEEP	1
8-76-03-92-92-8-2						PART NO		DESCRIPTION	ITEM NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	K.FOLTZ		05/31/94	<b>TE Connectivity</b>					
DIMENSIONS: mm [INCHES]		CHK	R.STONE		06/16/94						
		APVD	T.COULSON		06/17/94						
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		NAME			CONNECTOR KIT, UNASSEMBLED, 34 POSN, M SERIES				
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		APPLICATION SPEC		SIZE							CAGE CODE
MATERIAL		FINISH		WEIGHT		A300779		C-203736			
CUSTOMER DRAWING				SCALE		2:1		SHEET		1 OF 1	
				REV		AV1					

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)