
## **RT-375**

Single Wall tube with a 150°C operating temperature. A high level of clarity for enhanced visibility of substrates.



#### **PRODUCT DIMENSIONS**

SIZE	Inside Diameter as supplied (min) mm (inch) D	Inside Diameter after recovery (max) mm (inch) d	Wall Thickness after recovery (nom) mm (inch) W	Wall Thickness Tolerance after recovery mm (inch)
3/64	1.17 (.046)	0.58 (.023)	0.25 (.010)	0.10 (.004)
1/16	1.6 (.063)	0.79 (.031)	0.25 (.010)	0.10 (.004)
3/32	2.36 (.093)	1.17 (.046)	0.25 (.010)	0.10 (.004)
1/8	3.17 (.125)	1.57 <i>(.062)</i>	0.25 (.010)	0.10 (.004)
3/16	4.74 (.187)	2.36 (.093)	0.25 (.010)	0.10 (.004)
1/4	6.35 <i>(.250)</i>	3.17 (.125)	0.30 (.012)	0.15 (.006)
3/8	9.5 <i>(.375)</i>	4.74 <i>(.187)</i>	0.30 (.012)	0.15 <i>(.006)</i>
1/2	12.7 (.500)	6.35 <i>(.250)</i>	0.30 (.012)	0.15 (.006)
3/4	19.05 <i>(.750)</i>	9.5 <i>(.375)</i>	0.43 (.017)	0.15 <i>(.006)</i>
1	25.4 (1.000)	12.7 (.500)	0.48 (.019)	0.15 (.006)
1-1/2	38.1 (1.500)	19.05 <i>(.750)</i>	0.51 (.020)	0.15 <i>(.006)</i>
2	50.8 (2.00)	25.4 (1.00)	0.51 (.020)	0.15 (.006)

RT-375 – STANDARD SIZE REFERENCE DIMENSIONAL DRAWING			©2020		TE Connectivity Ltd. family of companies All Rights Reserved				
				DIMENSIONS IN mm (Inch)		5 – IRRADIATED MODIF OLYMER SINGLE WAL SHRINK TUBING			
Α	INITIAL REVISION	HD	14/10/2021	SHEET	NO DT 075		REV		
REV	ENGINEERING CHANGE	CHK	DATE	1 of 2	KI-3/5	<ul> <li>Standard Sizes</li> </ul>	Α		

### **RT-375**

#### PRODUCT INFORMATION

General use single wall Fluoropolymer Tubing. Shrink Ratio – 2:1 Longitudinal Shrinkage on full recovery – 0 to -10% Material conforms to TE Specification RT-375 Standard Colour: Clear Flame Retardant

Tubing cut to specific lengths can be supplied from the product sizes referenced within this drawing.

Cut length tolerances are as per the following table:

STANDARD CUTTING TOLERANCES (mm)				
CUT LENGTH	TOLERANCE			
Up to 9.9mm	±0.5mm			
10mm to 24.9mm	±1.0mm			
25mm to 54.9mm	±1.5mm			
55mm to 99.9mm	±3.0mm			
100mm to 149.9mm	±4.0mm			
150mm to 499.9mm	±5.0mm			
500mm to 1200mm	±12.5mm			



SHEET

### 单击下面可查看定价,库存,交付和生命周期等信息

# >>TE Connectivity(泰科)