

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
B		ECR-15-015267	19OCT2015	DW	CW
C		ECR-21-111798	02SEP2021	WQR	CW
C1		ECR-22-152753	21SEP2022	WQR	CW
C2		ECR-24-202368	12MAR2024	RW	CW

TYPE 1, T2050323201-000 T2050323201-001
 类型 1, T2050323201-000 T2050323201-001

NOTES:

1. TECHNICAL CHARACTERISTICS:
 INSULATION MATERIAL: PC
 RATED VOLTAGE: 400V
 RATED CURRENT: 16A
 INSULATION RESISTANCE: $\geq 400M\Omega$
 RATED IMPULSE VOLTAGE: 6KV
 POLLUTION DEGREE: 3
 FLAMMABILITY: UL94V-0
 MATING CYCLES: 500 CYCLES
 OPERATION TEMPERATURE: $-40^{\circ}C \sim +125^{\circ}C$
 WIRE RANGE: $0.14mm^2 \sim 4mm^2$ (AWG26-AWG12)
 CONTACT TYPE: CRIMP CONTACT


2. CONTACTS NEED TO BE ORDERED SEPARATELY.
 (ORDER No. REFER TO DRAWING: T20300X20XX000)

注释:

1. 技术参数:
 绝缘材料: PC
 额定电压: 400V
 额定电流: 16A
 绝缘电阻: $\geq 400M\Omega$
 脉冲电压: 6KV
 污染等级: 3
 阻燃等级: UL94V-0
 插拔次数: 500次
 工作温度: $-40^{\circ}C \sim +125^{\circ}C$
 接线范围: $0.14mm^2 \sim 4mm^2$ (AWG26-AWG12)
 接线类型: 冷压接

2. 端子需要单独订购。
 (订货号参考图面: T20300X20XX000)

PANEL CUT FOR INSERTS FOR USE
 WITHOUT HOODS/ HOUSINGS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 18DEC2014 RAGHAVENDRA H M	 TE Connectivity	
DIMENSIONS: mm		CHK 18DEC2014 CHRIS WANG		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 18DEC2014 XU XIANG	PRODUCT SPEC 108-137068	
0 PLC \pm		APPLICATION SPEC 114-137068		SIZE A3
1 PLC \pm		WEIGHT -		CAGE CODE 00779
2 PLC \pm		Customer Drawing		DRAWING NO T2050323201000
3 PLC \pm		SCALE 1:1		RESTRICTED TO -
4 PLC \pm		SHEET 1 OF 2		REV C2
ANGLES \pm				
FINISH -				
MATERIAL -				

1470-19 (3/13)

Downloaded From Onevac.com

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

REVISIONS

© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-


TYPE 2, T2050323201-002
类型 2, T2050323201-002

NOTES:
4X M3 SELF-TAPPING SCREW SEE THIS SHEET,
OTHER SPEC REFER TO TYPE 1.

注释:
4X M3 自攻螺丝参照此页, 其余产品规范参照类型 1.

4X M3 SELF-TAPPING SCREW, RECOMMENDED
TIGHTENING TORQUE 1.2~1.5N.m
4X M3 自攻螺丝, 推荐拧紧力矩 1.2~1.5N.m

T2050323201-002	HEEE-032-F	HEEE-032 FEMALE INSERT, SELF-TAPPING HEEE-032母插, 自攻螺丝	TYPE-2 类型-2
T2050323201-001	HEEE-032-F	HEEE-032 FEMALE INSERT WITH STAINLESS STEEL SCREW HEEE-032母插, 带不锈钢螺丝	TYPE-1 类型-1
T2050323201-000	HEEE-032-F	HEEE-032 FEMALE INSERT HEEE-032母插	
PART NUMBER 料号	PART DESCRIPTION 描述		TYPE 类型

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 18DEC2014 RAGHAVENDRA H M	 TE Connectivity	
DIMENSIONS: mm		CHK 18DEC2014 CHRIS WANG		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 18DEC2014 XU XIANG	PRODUCT SPEC 108-137068	
0 PLC ±-		MATERIAL -	APPLICATION SPEC 114-137068	
1 PLC ±-			WEIGHT -	
2 PLC ±-			SIZE CAGE CODE DRAWING NO RESTRICTED TO A3 00779 C-T2050323201000 -	
3 PLC ±-			SCALE 1:1 SHEET 2 OF 2 REV C2	
4 PLC ±-		Customer Drawing		
ANGLES ±-				
FINISH				

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)