

	Γ	3	.125	.318	.184	.100	1	2	4-873	348 – 3
		2			4.840	4.000	40	40	4-	-2
/ 5	OBSOLETE				4.840	4.000	40	40	4-	— 1
					3.984	3.900	39	40	4-	-0
					3.884	3.800	38	39	3—	_9
					3.784	3.700	37	38	3—	-8
					3.684	3.600	36	37	3—	-7
					3.584	3.500	35	36	3-	-6
					3.484	3.400	34	35	3-	-5
					3.384	3.300	33	34	3-	-4
					3.284	3.200	32	33	3—	-3
					3.184	3.100	31	32	3—	-2
					3.840	3.000	30	31	3—	— 1
					2.984	2.900	29	30	3-	-0
					2.884	2.800	28	29	2-	_9
					2.784	2.700	27	28	2-	-8
					2.684	2.600	26	27	2-	-7
					2.584	2.500	25	26	2-	-6
					2.484	2.400	24	25	2-	-5
					2.384	2.300	23	24	2-	-4
					2.284	2.200	22	23	2-	-3
					2.184		21	22	2-	-2
					2.084	2.000	20	21	2-	— 1
					1.984	1.900	19	20	2-	-0
					1.884	1.800	18	19	1-	-9
					1.784	1.700	17	18	1-	-8
					1.684	1.600	16	17	1-	-7
					1.584	1.500	15	16	1-	-6
					1.484	1.400	14	15	1-	-5
					1.384	1.300	13	14	1-	-4
					1.284	1.200	12	13	1-	-3
					1.184	1.100	1 1	12	1-	-2
					1.840	1.000	10	11	1-	— 1
					.984	.900	9	10	1-	-0
					.884	.800	8	9		_9
					.784	.700	7	8		-8
					.684	.600	6	7		-7
					.584	.500	5	6		-6
					.484	.400	4	5		-5
					.384	.300	3	4		-4
					.284	.200	2	3		-3
					.184	.100	1	2		-2
		2	.125	.318	.084	0	0	1	873	348-1
RE		FINISH	E	D	С	В	A	NO OF POS	ASSE PA NUM	RT
	THIS DRAWING IS A	A CONTROLLED DOCUMENT.			6-89 6-89 ETE TE Connectivity					
		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± -	R. FE APVD R. FE PRODUCT	EIDT spec	6-89 NAME	ASSEMBLY, .100 C/			SINGLE RC SQ POSTS	
	Ψ	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	APPLICAT	ION SPEC	SIZE	CAGE CODE DRAV	VING NO	_	R	ESTRICTED TO
	MATERIAL	FINISH	A = A = A = A = A = A = A = A = A = A =							

2

DIST

38

LOC

AD

REVISIONS DESCRIPTION

L PLASTIC MATERIAL SUPPLIER CHANGED FOR HOUSING

07MAY2021 SB KJK

4			3	
THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	-,		
C COPYRIGHT – By –	ALL RIGHTS RESERVED.			

D

С

В

А

	4	.125	.318	3.984	3.900	39	40	9-873	548 —C
				3.884	3.800	38	39	8-	
Γ				3.784	3.700	37	38	8-	-8
				3.684	3.600	36	37	8-	-7
				3.584	3.500	35	36	8-	-6
				3.484	3.400	34	35	8-	-5
-				3.384	3.300	33	34	8-	-4
+				3.284	3.200	32	33	8-	
+				3.840	3.100 3.000	31	32	8-	-2
+				2.984	2.900	30 29	31	8— 8—	<u> </u>
				2.884	2.800	29	29	7-	
ł				2.784	2.700	28	29	7-	-8
				2.684	2.600	26	27	7-	
F				2.584	2.500	25	26	7-	
- F				2.484	2.400	24	25	7-	
Ť				2.384	2.300	23	24	7-	Z
Ī				2.284	2.200	22	23	7—	— (
Ī				2.184	2.100	21	22	7—	-2
				2.084	2.000	20	21	7—	
				1.984	1.900	19	20	7—	-0
Ļ				1.884	1.800	18	19	6-	-9
				1.784	1.700	17	18	6-	-8
-				1.684	1.600	16	17	6-	
- F				1.584	1.500	15	16	6-	-6
-				1.484	1.400	13	15	6— 6—	5 2
				1.284	1.200	12	14	6-	
-				1.184	1.100	1 1	12	6-	-2
F				1.840	1.000	10	1 1	6-	
				.984	.900	9	10	6-	-(
l l				.884	.800	8	9	5-	_9
				.784	.700	7	8	5-	-8
				.684	.600	6	7	5-	-7
				.584	.500	5	6	5-	-6
				.484	.400	4	5	5-	-5
-				.384	.300	3	4	5-	4
-				.284	.200	2	3	5-	-3
-		.125	Z 1 0	.184	.100	1	2	5- 1	-2
-	4	.120	.318	.084	0	0		5-873	
		E	D	С	В	A	NO	ASSEN	
	FINISH					<i>, , , ,</i>	OF	PAF	
							POS	NUM	BER
THIS DRAWING IS A	CONTROLLED DOCUME	NT. DWN K HE	LM	6-89			+ 		
DINENCIONS	TOUED MIDEO	CHK							
DIMENSIONS: INCHES	OTHERWISE SPECIFIE	TOLERANCES UNLESS DTHERWISE SPECIFIED: APVD R. FEIDT							
1	0 PLC ± - 1 PLC ± -		PRODUCT SPEC ASSEMBLT, MOD II, HEADLIN, SINGLE NOW, .100 C/L, VERTICAL, .025 SQ POSTS						,
	12 PLC $\pm -$		ON SPEC			,	_		

DIST AD 38

LTR

_

LOC

2

REVISIONS DESCRIPTION DATE DWN APVD SEE SHEET 1 _ ____ _

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)