



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION.
- DUST COVER IS INSTALLED FOR SHIPPING.
- KEYING SHOWN IN POSITION "01" FOR ILLUSTRATION ONLY. CONNECTORS SHIPPED WITH KEYING INSTALLED IN POSITION PER TABLE. FOR POSITION "00" KEYING HARDWARE SHIPPED UNASSEMBLED.
- WITH CONTACT FULLY SEATED IN CAVITY.
- CONTACTS NOT SHOWN IN FRONT & REAR VIEWS FOR CLARITY, EXCEPT SIZE 8 QUADRAZ.
- FOLLOWING CONTACTS ARE INCLUDED AND LOADED:
 - MODULE A:
P/N 211431-4; SIZE 22 POSTED SOCKET CONTACT; QTY = 150.
 - MODULE B:
P/N 1445626-4; SIZE 8 POSTED QUADRAZ CONTACT; QTY = 11
 - MODULE C:
P/N 1-448138-2; SIZE 20 POSTED PIN CONTACT; QTY = 4
P/N 1-448139-4; SIZE 16 POSTED PIN CONTACT; QTY = 3
P/N 1-448140-8; SIZE 112 POSTED PIN CONTACT; QTY = 4
P/N 1445626-4; SIZE 8 POSTED QUADRAZ CONTACT; QTY = 2

COMPONENT	MATERIAL	FINISH
SHELL	DIE CAST ALUMINUM PER ASTM-B-85	ELECTROLESS NICKEL PER MIL-C-26074
RETENTION PLATES	ALUMINUM ALLOY PER ASTM-B-209	ELECTROLESS NICKEL PER MIL-C-26074
SCREWS AND LOCKWASHERS	STEEL OR STAINLESS STEEL	CHROMATE OVER ZINC OR PASSIVATED
POLARIZING KEYS	ZINC ALLOY PER ASTM-B-86	-
POLARIZING KEY RETAINING PLATE	ALUMINUM ALLOY PER ASTM-B-209	BLUE ANODIZED PER MIL-A-8625
11Q11 INSERT	ALUMINUM ALLOY	ELECTROLESS NICKEL PER MIL-C-26074
150 & 11Q2 INSERTS	THERMOSET OR PPS	-

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN C.C.THOMAS 3-24-05	3-29-05		Tyco Electronics Corporation Harrisburg, Pa 17105-3608
0 PLC ± -	1 PLC ± -	CHK K.HOGAN 3-29-05	3-29-05		NAME
2 PLC ± .01 [0.3]	3 PLC ± .005 [0.13]	APVD K.HOGAN 3-29-05	PRODUCT SPEC	RCPT ASSY, SIZE 2, ARINC 600 (150/11Q11/11Q2) WITH QUADRAZ CONTACTS	RESTRICTED TO
4 PLC ± -	ANGLES ± -	APPLICATION SPEC	WEIGHT	SIZE A1 00779	DRAWING NO. 1757748
MATERIAL SEE TABLE	FINISH SEE TABLE	CUSTOMER DRAWING	SCALE 1.5:1	SHEET 1 of 1	REV O

01	1757748-1
KEYING POSITION	PART NUMBER

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)